

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; & 25 of T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7191)

-----  
Set quarter sec. post, from which  
A Pine 18" dia., bears S.31°W., 55 lks. dist.  
A Pine 25" dia., bears N.42°E., 155 lks. dist.

A. R. Evans - For: K. Kartes - Witness: G.E. Johnson - June 14, 1953 - C.S. File 41/252-2

-----  
Set by proportional measurement.  
Set 4" x 4" x 36" Pine stake in mound of rock.  
New BTs -14" Pine N.68°W., 27.7 ft. mkd. ¼ S25 - RE 2741 BT.  
14" Pine N.74½°E., 54.8 ft. mkd. ¼ S30 RE 2741 BT.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. file 53/40-33

-----  
Found - Both bearing trees recorded by Evans. Bearing trees OK. We find mound of stone at corner.  
Set brass cap at cor. mkd: County Surveyor's Office 1963  
¼ R7W S25 | S30 R6W T30S

BLM resurvey by Jelley and Akin, under Group #'s 734 and 829 Surveyed April 1971/Oct. 1973 (DCSO records, Vol. 37 Pages 15140-41)

-----  
(CORNER REPORT ONLY)  
The ¼ Cor. reestablished by Evans in 1953 & subsequently perpetuated by Byron in 1963. This position is harmoniously related to existing original corners, has been recognized as the corner by adjacent landowners & is accepted as the best available evidence of the original corner position. Corner monumented with a 1963 DCSO brass cap, properly mkd. from which bearing trees mkd. by Evans  
A Pine 18" dia., bears N.74¼°E., 82 lks. dist., with fragmentary scribe marks vis. on partially opened blaze  
A Pine 15" dia., bears N.67 ¾°W., 43 lks. dist., with fragmentary scribe marks vis. on partially opened blaze

Mark Smalley - For: Roseburg Resources - June 1999 - M 133-9

-----  
Found - 1963 County brass cap on IP also mkd: BLM 1971  
17" J.Pine, N.67 ¾°W., 28.4 ft. scribe visible.  
21" J.Pine, N.74¼°E., 54.1 ft. healed.  
New BTs- 16" J.Pine, S.40°W., 29.3 ft. "¼ S BT"  
16" J.Pine, N.12°W., 46.2 ft. "¼ S BT"