TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 19; & 24, T30-7

Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7190

Set quarter sec. post, from which
Cedar 15" dia., bears N.40°W., 11 lks. dist.
Cedar 6" dia., bears N.20°E., 126 lks. dist.

Claude Kerr, Engineer - June 6, 1953 - C.S. File 41/160

Found the original Incense Cedar BT, bearing N.20°E. for 126 lks. Chopped in and found old scribe markings. This is now a 24" Cedar.
Set a Cedar stake for the ¼ cor. mkd. "¼ S24 and 19"

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/40-35

Found - Mound of stone and stake at corner.
Orig. 6" now 24" Cedar, N.20°E., 83.2 ft. previously opened, good scribing.
Orig. NW BT, down & mostly rotted.
Set Brass cap at cor. mkd: County Surveyor's Office, 1963
¼ S24|S19 T30S
R7W R6W
New BTs -10" R.Fir bears N.7°W., 14.0 ft. scribed ¼ S24 CSBT
12" Cedar bears S.81°E., 19.4 ft. scribed ¼ S19 CSBT
Corner is under 18" Cedar log.

Mark Smalley - For: Roseburg Resources Co. - 2/1999 - M129-43

Found - 1963 County brass cap on IP
24" Cedar snag N.20°E., 84.1 ft.(83.2 ft.)scribe visible. OBT
10" Fir N.7°W., 14.0 ft., dead, broken stub.
12" Cedar S.61°E. (S.81°E.) 19.4 ft. scribe vis.
Scribed- 14" Fir N.89°E., 30.0 ft., "¼ S BT"
14" Fir S.6°W., 22.4 ft., "¼ S BT"
8" Fir N.53°W., 29.6 ft., "¼ S BT"
13" Cedar N.33°E., 43.3 ft., "¼ S BT"

Brent Knapp - For: Roseburg Resources Co. - 8/2023 - M182-53

Found - 1963 DCSO brass cap
14" Fir snag, healed scar & tag; N.89°E., 30.0'
15" Cedar, healed scar & tag; N.33°E., 43.3'
Metal post; North 1'
New - 10" Fir, scribed "¼ S19 BT"; N.19°E., 33.0'
7" fir, scribed "¼ S24 BT"; S.42°W., 26.6'_____