TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 18; Sec. 13, T30-7

Alias Description
Alias Description
Alias Description
Alias Description

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7190)

Set quarter sec. post, from which
Laurel 6" dia., bears N.30°W., 6 lks. dist.
W.Fir 8" dia., bears N.70°E., 21 lks. dist.

BLM resurvey by Jelley and Akin, under Group #'s 734 and 829 Surveyed April 1971/Oct. 1973 (DCSO records, Vol 37 Pg 15143)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:

T 30 S
1/4
S 7 W|R 6 W
S 13|S 18
1973

from which
A W.Fir 15" dia., bears S.89°E., 58 lks., mkd. ¼ S18 BT.
A W.Fir 18" dia., bears S.11½°W., 31 lks., mkd. ¼ S13 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2191, Surveyed April/May 2008 - (DCSO records Vol. 56 Page(s) 22128-9)

The ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Jelley and Akin
A decayed fir stump, size indeterminate, bears S.89°E., 38.3 ft., with scribe marks 1/ and other fragmentary marks visible on a partially healed blaze.
and new bearing trees
A fir, 8" dia., bears N.87¾°E., 11.0 ft., mkd. ¼ S18 BT.
A fir, 14" dia., bears N.15°W., 43.6 ft., mkd. ¼ S13 BT.