

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7189)

Set post, cor. to secs. 6, 7, 1 and 12, from which
A Pine 36" dia., bears N.45°W., 12 lks.
A Laurel 20" dia., bears S.3°W., 63 lks.
A Laurel 22" dia., bears S.87°E., 123 lks.
A Laurel 25" dia., bears N.45°E., 104 lks.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby - sept. 13, 1963 - C.S. File 49/139-107

Found - Orig. 36" now 42" Pine N.45°W., 7.9 ft., shows good scribing.

Orig. SW BT, now dead, checks record bearing & dist.

Orig. 22" now 30" Laurel, shows good scar, S.82°E., not S.87°E., 81.2 ft.

Orig. 25" now 32" Laurel, shows good scar, N.50°E., not N.45°E., 68.6 ft.

Set B. cap at cor. mkd: County Surveyor's R7W

S 1	S6
S12	S7

 R6W
Office 1963

New BTs -10" W.Fir bears N.81°E., 5.4 ft. scribed S6 T30S R6W
CS BT.

7" R.Fir bears S.25°E., 22.5 ft. scribed S7 CS BT.

12" W.Fir bears S.58°W., 21.2 ft. scribed S12 T30S
R7W CS BT.

BLM resurvey by Jelley and White, under Group #'s 350 & 551 Surveyed May 1963-July 1964 (DCSO records, Vol. 32 Pages 13583-84)

The Sec. cor., perpetuated and recorded by Byron, 1963, monumented with an I.P. 1" dia., 14" above ground, firmly set, with properly mkd. brass cap.

from which original bearing trees

A Madrone 34" dia., bears N.49°E., 106 lks. dist., with healed blaze. (Rec. brg & dist., N.45°E., 104 lks.)

A Madrone 34" dia., bears S.82°E., 125 lks. with illegible scribe marks visible on partially healed blaze. (Rec. S.87°E., 123 lks.)

A dead Madrone 22" dia., bears S.3°W., 63 lks. with illegible scribe marks visible on opened blaze.

A Pine 48" dia., bears N.45°W., 16 lks. dist., with scribe marks T30 R7W S1 BT visible on partially healed double blaze. (Rec. dist. 12 lks.)

and bearing trees by Byron

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T30-7

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A W.Fir 10" dia., bears N.81°E., 8½ lks. dist., with scribe marks T30S R6W S6 CS BT visible on double blaze.
A Fir 9" dia., bears S.25°E., 34 lks. dist., with illegible scribe marks visible on partially healed double blaze.
A W.Fir 13" dia., bears S.58°W., 32½ lks. dist., with scribe marks T30S R7W S12 CS BT visible on double blaze.
Add marks BLM 1964 to bottom of brass cap.

See BLM for a 1977 Administrative survey

Howard Johnstone - For: Roseburg Lumber Co. - June 6, 1977
(added to record 11/30/2023) -M 65-27

Found - 1963 County BCIP
16" Fir N.75°E., 5.4
18" Fir S.57¾°W., 20.8
12" Fir S.24°E., 21.8
48" Pine N.45°W., 7.9 (Down) OBT

David Edwards - 11/2023 - CS File 65/113-21

Found - Standard 1963 DCS0 brass capped iron pipe in good condition.
A 26" dia. Fir w/healed blase bears S.24°E., 21.8'
A 24" dia. Fir snag w/healed blaze bears S.57¾°W., 20.8'.
All other previous B.T.'s are gone.
New - A 6" dia. Fir scribed "S12 BT" bears S.39°W., 12.7'
A 6" dia. Fir scribed "S1 BT" bears N.73°W., 19.1'
A 5.5 foot steel post is set 2 feet East.
Note - Compass Declination 15° East.