

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; & S. 6, T31-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

above ground, with an aluminum cap mkd. R.R. CO. T30S R7W 1/4 S31 S6 T31S 1992 LS 2354, from which the remains of bearing trees reported by Jelley

A maple, 26" dia., bears S.61 $\frac{3}{4}$ °E., 311.8 ft., with illegible scribe marks visible on decayed partially healed blaze. (Record, S.60°E., 283.8 ft.)

A hollow pine stump, 28" dia., bears N.38 $\frac{1}{4}$ °W., 99.0 ft., with illegible scribe marks visible on decayed blaze. (Record, N.36 $\frac{1}{2}$ °W.)

and the remains of the bearing trees mkd. by Smalley

A fir, 38" dia., bears S.77 $\frac{1}{2}$ °E., 222.7 ft., with a healed blaze.

A decayed fir stump, 34" dia., bears N.19°W., 117.7 ft., with a healed blaze.

At the corner point

Remove the iron rod from the area and set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 22" in the ground, with brass cap mkd.

T 30 S

R $\frac{1}{4}$ S 31
6 S 6

W

T 31 S

2018

from which a new bearing tree

A pine, 10" dia., bears N.76 $\frac{3}{4}$ °W., 32.6 ft., mkd. $\frac{1}{4}$ S31 BT. Corner is located on level ground.