

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 31

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Mark Smalley - For: Roseburg Resources - July, 1992, M 112-52

Set 2" brass tablet in rock.

New Accessories:

5" Oak bears S.62°E., 13.6 ft. scribed "C¹/₄ S31 BT".

7" Oak bears N.63°E., 8.3 ft. scribed "C¹/₄ S31 BT".

6" Oak bears N.37°W., 21.8 ft. scribed "C¹/₄ S BT".

6" Oak bears N.24°E., 21.2 ft. scribed "C¹/₄ S BT".

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2928 - surveyed July /Aug. 2018 - (DCSO records Vol. 59 Page(s) 23663

The center ¹/₄ sec. cor. of sec. 31, established by Smalley, in 1992; and is accepted as the cor.; monumented with a brass tablet, 2" dia., cemented in a drill hole in solid rock, with top mkd.

T 30 S R 6 W

S 31

C ¹/₄

1992

LS 2354

from which the remains of the bearing trees mkd. by Smalley
An oak, 7" dia., bears N.17¹/₂°E., 21.1 ft., with a healed blaze.

An oak, 9" dia., bears N.64¹/₄°E., 8.4 ft., with a healed blaze.

An oak, 6" dia., bears S.66¹/₂°E., 13.4 ft., with a healed blaze.

An oak snag, 8" dia., bears S.40¹/₂°E., 21.6 ft., with scribe marks B and other illegible scribe marks and a 3/4" dia., brass tag mkd. LS 2354, visible on partially healed blaze.

The cement around the brass tablet is mkd. OLSON RADDATZ WHITE JULY 1, 1992.

Corner is located on rocky bluffs on S. facing slope.