

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7220)

Set quarter sec. post, from which
A Pine 36" dia., bears N.70°W., 31 lks. dist.
A Pine 30" dia., bears S.30°W., 20 lks. dist.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - July/Aug. 1961 - C.S. File 42/288-2

1/4 Cor. as determined by O.B.T
38" Pine N.70°W., 20.4 ft., found scribe.
At corner point set 3/4" x 30" I. Rod, from which
7" Pine bears N.6°W., 9.0 ft. ¼ S30 BT.
18" Pine bears N.52°E., 26.2 ft. ¼ S30 BT.
7" Cedar bears S.14°E., 23.8 ft. ¼ S31 BT.
14" Pine bears S.39°E., 60.6 ft. ¼ S31 BT.

Fd. OK, Mark Smalley, July 1992, M 112-52

Mark Smalley - For: Roseburg Resources Co. - June 1999 - M 133-9

Found - 3/4" Iron rod.
9" I.Cedar S.14°E., 23.8 ft., scribe visible.
18" Pine, N.52°E., 26.2 ft., staub.
36" Pine, N.70°W., 20.5 ft. root hole, orig.
16" Pine, S.39°E., 60.6 ft. healed, poor condition.
New BT - 6" Pine, N.10°W., 4.5 ft. "¼ S BT"
7" Pine, S.63°W., 23.3 ft., "¼ S BT"

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2928 - surveyed July /Aug. 2018 - (DCSO records Vol. 59 Page(s) 23664-5)

The ¼ sec. cor. of secs. 30 and 31, perpetuated by Markham Jr., in 1961; subsequently perpetuated by Smalley, in 1999; monumented with an iron rod, ¾" dia., 30" long, firmly set, projecting 5" above ground, no cap, from which the remains of an original bearing tree

A roothole, bears N.70°W., 20.5 ft., alongside of which is a down decayed pine, size indeterminate, with scribe marks ¼ S X BT visible on open blaze.

and the remaining bearing trees mkd. by Markham

A cedar, 10" dia., bears S.17¾°E., 23.3 ft., with scribe marks ¼ and other illegible scribe marks visible on partially opened blaze. continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A pine, 18" dia., bears S.41 $\frac{3}{4}$ °E., 59.7 ft., with a healed blaze.
and the bearing trees mkd. by Smalley
A pine, 10" dia., bears S.62 $\frac{1}{2}$ °W., 23.3 ft., with a healed blaze.
A pine, 10" dia., bears N.16°W., 4.1 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 23" in the ground, in a collar of stone, with brass cap mkd.
T30S R6W
 $\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$
2018
Remove and dispose of the iron rod.
Corner is located on a SW facing slope.
The geographic position in NAD 1983 (2011)
Latitude: 42°55'39.38" N. Longitude: 123°27'23.20" W.