

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 18 and 19

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7223)

-----  
Set quarter sec. post, from which a  
Pine 36" dia., bears N.89°E., 144 lks. dist.  
Pine 30" dia., bears S.47°E., 217 lks. dist.

Clifford M. Brydon - Feb. 13, 1957 - C.S. File 42/251

-----  
Found scribe marks on old down Pine.  
Marked new witness trees:  
Fir 8" dia., N.28°E., 7.9 ft.  
Cedar 6" dia., S.14½°E., 4.5 ft. scribed R.E. 3937 B.T.

Douglas Co. Surveyors Office - James W. Byron, deputy - Mike Darby; Jim Halterman - Nov/Dec 1963 - C.S. File 53/40-6

-----  
Found - BTs as recorded and stake at corner.  
Set Brass cap at cor. mkd: County Surveyors ¼ S18 T30S R6W  
Office, 1963 S19  
No new bearing trees marked.

Mark Smalley - For: Roseburg Resources Co. - Feb. 1999 - M129-43

-----  
Found - 1963 County brass cap on iron pipe.  
Rotted Fir stub N.28°E., 7.9 ft.  
Cedar stub S.14½°E., 4.5 ft.  
Scribed- 21" I.Cedar S.52°E., 7.2 ft., "¼ S BT"  
24" I.Cedar S.28°W., 28.7 ft., "¼ S BT"  
16" D.Fir N.70°E., 40.6 ft., "¼ S BT"  
8" D.Fir S.30°W., 39.2 ft., "¼ S BT"

Fd. Ok by K. DeGroot - Oct. 2000 - M 136-1