

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T31-6

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7194)

-----

Set post, cor. to secs. 31, 32, 5 & 6, from which

- A Laurel 8" dia., bears N.86°E., 19 lks.
- A Laurel 6" dia., bears N.3°W., 40 lks.
- A Laurel 5" dia., bears S.38°E., 25 lks.
- A Red Fir 25" dia., bears S.85°W., 30 lks.

Cor. Fd. and used in GLO survey by W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Pg. 8016)

BLM dependent resurvey by James Jelley, under Group #585 - Surveyed July/Aug. 1965 (DCSO records, Vol. 33 Page 13813)

Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:

T 30 S R 6 W
<u>S 31   S 32</u>
S 6   S 5
T 31 S
1965

from which

- An Oak 10" dia., bears N.73°E., 36 lks. dist., mkd. T30S R6W S32 BT.
- A Fir 8" dia., bears S.62°E., 26 lks. dist., mkd. T31S R6W S5 BT.
- A Fir 18" dia., bears S.16°W., 28 lks. dist., mkd. T31S R6W S6 BT.
- A Fir 15" dia., bears N.3½°W., 26 lks. dist., mkd. T30S R6W S31 BT.

The corner is located on a ravine, drains N.65°W.

Fd. OK, July 1992, Mark Smalley, M 112-52  
Found OK by K. DeGroot, Dec. 2000 - LP 2000-0092 A&B

Greg Lang - For: Roseburg Resources - 5/16/2006 - M150-53 & C.S. File 65/58-17A

-----

Found - 1965 BLM brass cap.  
A 27" D.Fir bears N.5½°W., 17.16 ft.  
The other trees are down or gone.

continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T31-6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - A 21" D.Fir bears S.27½°E., 41.10 ft scribed "T31S R6W S5 BT"  
A 13½" Madrone bears N.53½°E., 39.80 ft scribed "T30S R6W S32 BT"  
A set 5/8"x 30" iron rod bears S.68°W., 33.00 ft.  
This bearing object is marked by a steel post and BT tag.

Note - There are spikes in the base of all BTs for measuring distances to the corner; bearings to the trees were measured with a total station & are based on the original survey line between Sections 31 & 32.  
Corner lies in the bottom of a draw with a logged unit to the West.