

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7219)

Set post, cor. to secs. 29, 30, 31 and 32, from which
A B.Oak 24" dia., bears S.56°W., 191 lks. dist.
A B.Oak 15" dia., bears N.7°E., 362 lks. dist.
A B.Oak 15" dia., bears N.78°W., 232 lks. dist.
No trees SE convenient.

J. W. Cole, Surveyor - Ben Irving, Chain - For: Percy Webb - Jan. 23, 1924 - Field Book 52 Pg. 29

I set a granite rock 10" x 12" x 18" marked CS and 5 notches on east side, one notch on south side, from which remains of old tree fallen and decayed showed all scars, bears N.6°30'E., 239.0 ft.
24" B.Oak alive, bearing scars, N.78°W., 153.0 ft.
A stump of 40" B.Oak in which I found old face with scribe mark B, bears S.60°W., 126.0 ft.
Marked boulder 4 ft. x 8 ft. "CS BO" N.36°E., 52.2 ft.
A W.Oak N.47°W., 20.0 ft.
An 8" W.Oak S.19°15'W., 36.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - CS File 53/40-2

Found - Stone at corner and all bearing trees.
Set Brass cap alongside cor. stone & mkd:
County Surveyors Office S30|S29 T30S R6W
1963 S31|S32
Rescribe 18" W.Oak bears N.48°W. 21.0 ft "S30 T30S R6W CS BT"

Found OK, Larry Dolan, June 1988, M 106-47
Found OK, Mark Smalley, July 1992, M 112-52
Found OK Oct. 1998 by G. Nygren - M129-23
Found OK by K. DeGroot, Dec. 2000 - LP 2000-0092 A&B

DCSO-GIS Corner visitation - 3/1/2004 - Typed: 2/9/2011 - C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK

Greg Lang - For: Roseburg Resources - 5/16/2006 - M150-53 & C.S. File 65/58-17A

Found - The corner stone and a brass cap which bears S.66°49'07"E 0.63 ft. continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 12" W.Oak bears S.16°W., 36.50 ft.
A 13½" D.Fir bears N.86°W., 23.50 ft.
A 20" W.Oak bears N.49½°W 21.00 ft.
A rock (bearing object) bears N.36°E., 52.20 ft.
New - A 21½" Pine bears S.71°E., 252.10 feet scribed "T30S
R6W S32 BT
Note - There are spikes in the base of all BTs for
measuring distances to the corner; bearings to
the trees were measured with a total station &
are based on the original survey line between
Sections 31 & 32.
Corner lies West of a small creek at the base of an
easterly slope.