

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7221)

Set quarter sec. post, from which
A Sugar Pine 15" dia., bears N.25°E., 36 lks.
A Sugar Pine 10" dia., bears N.8°W., 18 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Jim Halterman; Mike Darby - Jan.1964 - C.S. File 53/40-16

Found - Orig. 10" now 36" Pine N.8°W., 11.7 ft. We open & find good scribing.
Do not find NE BT.
Find 1" I.P. at corner.
Note - N-S fence 4 ft. West.
New BTs -12" Fir bears N.67°W., 20.3 ft. scribed ¼ S30 CS BT.
5" Fir bears N.41°W., 68.2 ft. scribed ¼ S29 CS BT.

Found OK Oct. 1998 by G. Nygren - M129-23

Mark Smalley - For: Roseburg Resources Co. - June 1999 - M 133-9

Found - 1" I.P.
41" Pine, N.8°W., 11.9 ft., face chopped, Orig.
20" Fir, N.67°W., 20.3 ft., healed.
New BTs- 8" Fir N.22°E., 22.0 ft. "¼ S BT"
12" Fir N.33°W., 37.0 ft. "¼ S BT"

Found OK by K. DeGroot, Dec. 2000 - LP 2000-0092 A&B