

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 19 and 20

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7222)

Set quarter sec. post, from which
A Pine 5" dia., bears S.50°W., 138 lks. dist.
A Pine 4" dia., bears N.75°E., 65 lks. dist.

Douglas Co. Surveyors Office - John M. Powell; J. Brady; F. Jones - Nov. 24, 1965 - C.S. File 53/40-26

Found - 5" Pine S.50°W., 138 lks. 91.1 ft. opened & found scribe "B". This tree rotten snag, also had been rescribed above the old face, scribe visible "B". This tree go for right size.
No trace of 4" Pine N.75°E., 42.9 ft.
14" Pine S.89°E., 52.8 ft. scribed "B" about 80 years ago by ring count. Tree faces about South.
No record of the tree.

Set Brass cap at cor. mkd: County Surveyors Office, 1965
T30S R6W ¼ S19 | S20
New BTs -9" Cedar N.52°W., 10.6 ft. scribed ¼ S19 CSBT.
12" Pine S.31°E., 15.3 ft. scribed ¼ S20 CSBT.

Found OK Oct. 1998 by G. Nygren - M129-23

Mark Smalley - For: Roseburg Resources Co. - Feb. 1999 - M129-43

Found - 1965 County brass cap on IP.
11" I.Cedar N.52°W., 10.6 ft., healed.
12" Pine S.31°E., 15.3 ft., scribe visible.
17" Pine S.89°E., 52.8 ft., faces South.
Scribed- 16" I.Cedar S.60°E., 33.2 ft., "¼ S BT"
16" I.Cedar N.29°E., 35.7 ft., "¼ S BT"