

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias <u>907030</u>	Description <u>Cor #2 M.S. #137</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7222)

Set post cor. to secs. 17, 18, 19 and 30, from which
A Pine 48" dia., bears S.75°W., 293 lks. dist.
A Pine 40" dia., bears N.85°W., 259 lks. dist.
A Pine 48" dia., bears N.22°E., 260 lks. dist.
A Pine 30" dia., bears S.75°E., 300 lks. dist.

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor for: Oakland Placer Nickel and Chrome Mine - Nov. 17, 1886 (DCSO records Vol. 28 Page(s) 11811)

Intersect section post cor. to secs. 17, 18, 19, and 20. Marked post No. (2) claim No. (38). Established new witness trees the old ones being incorrect, to wit:
A Pine 30" dia., bears S.79°E., 320 lks.
A Pine 40" dia., bears N.81°30'W., 290 lks
A Pine 48" dia., bears S.67°W., 300 lks.
A Pine 8" dia., bears N.27°30'E., 140 lks.

A. Boyer, D.C.S. - Wit: Geo. Piper; C. Harrison - For: Freeport Sulphur Co. - Nov. 12, 1942 - C.S. File 31/9

Found the three O.B.T.s but the one in SW quadrant was gone and stump only showing. Marked new trees:
A 12" Pine S.59°W., 31.0 ft.
A 12" Pine N.50°W., 4.0 ft.
Set a 4 x 4 post and a pile of rocks at corner.
Found a pile of rocks about 2 ft. North, O.B.T.
(See F.B. 104 Pg. 63 and M.S. Notes of Briggs)
A 30" Pine S.79°E., 320 lks.
A 40" Pine N.81°30'W., 290 lks.
A 48" Pine stump S.67°W., 300 ft.
An 8" Pine N.27½°E., 140 lks.
Drove post.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - May/June 1957 - C.S. File 42/269-4

Location of point for corner determined by O.B.T.s
A 15" Pine bears N.50°W., 4.0 ft.
A 12" Pine bears S.59°W., 31.0 ft., found scribe
A 24" Pine bears N.25°E., 95.5 ft., found scribe
Set an Iron pipe with brass cap in concrete at corner point mkd. T30S R6W 17-18-19-20, 2880, 1957, from which
18" Pine bears N.86°30'W., 29.7 ft. mkd. S18 BT.
32" Fir bears S.40°W., 54.2 ft. mkd. S19 BT.

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19, 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

8" Pine bears S.38°E., 12.1 ft. mkd. S20 BT.
Road bears North, 183.0 ft.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone - July 1964 - C.S. 53/40-55

Found - Old Pine, original BT.
Set Iron rod (temp. point) N.79½°W., 211.2 ft. (slope dist., slope approx. 6°). From Iron rod
A Pine (mineral survey BT) bears N.23½°E., 92.4 ft. slope dist., slope approx. 18°. Notes call for N.27½°E., 92.4 ft.
A Pine (mineral survey BT) bears N.83°W., 199. ft. (slope dist.) slope approx. 17°20' for 152 ft. balance level. Notes call for N.81½°W., 191.4 ft.
An old Pine stump (scribe mark "BT" on root) bears S.77½°W., 196.0 ft. slope dist., approx. 10° slope for 150 ft., balance level. Notes call for BT S.67°W., 198.0 ft.
Markham's brass cap bears S.80°W., 5.3 ft.

Douglas Co. Surveyors Office - V.R. Tracy & Crew - Sept 1964 - C.S. File 53/40-25

Found Iron rod recorded in July 1964. Remove iron rod and set Brass cap mkd: County Surveyors T30S R6W S18|S17
Office 1964 S19|S20
Markham's brass cap bears S.80°W., 5.3 ft.
Existing and new BTs:
38" Pine N.23½°E., 92.4 ft. on slope of 18°.
16" Pine S.83°W., 8.2 ft. healed over scar.
14" Pine S.8°E., 10.9 ft. mkd. T30S R6W S20 CS BT.
15" Pine N.44°W., 76.5 ft. on slope 19° mkd. T30S R6W S18 CS BT.

Douglas Co. Surveyors Office - Randall Smith; Stephen Flause; Terrie Franssen - May 7, 1991 - C.S. File 64/15-11

CORNER REPORT ONLY
Found - A 1964 DCS0 brass cap on a 1½" O.D. iron pipe protruding 4" above ground & properly mkd.
2½" dia. B/C is flush with ground bears S.80°W., 5.3 ft. (Markham BC)
16" now 21" dia. Pine with a fully healed double blaze bears N.82°W., 8.2 ft. (Rec. S.83°W., 8.2 ft.)
(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec Cor for 17, 18, 19 and 20

Alias 907030 Description Cor #2 M.S. #137
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

14" now 15" dia. Pine with 5 ft. of fill around base of tree. No blazes visible, bears S.8°E., 10.9 ft
15" now 24" dia. Pine with a fully healed double blaze bears N.44°W., 70.5 ft. (Rec. N.44°W., 76.5 ft.)
38" Pine bearing N.23½°E., 92.4 ft. is gone.
18" now 22" dia., Pine with a fully healed double blaze bears N.88½°W., 34.4 ft. (Rec. N.86½°W., 29.7 ft.)
24" now down & rotted Pine with stump of indeterminable size. No blazes or scribing visible bears N.22 3/4°E., 88.8 ft. (Rec. N.27¼°E., 92.4 ft.)
No new accessories.

Found OK Oct. 1998 by G. Nygren - M129-23

Mark Smalley - For: Roseburg Resources Co. - Feb. 1999 - M129-43

Found - 1964 County brass cap on IP.
20" Pine N.82°W., 8.2 ft., healed stub.
16" Pine S.8°E., 10.9 ft., healed stub.
24" Pine N.44°W., 70.5 ft., healed.
20" Pine N.88½°W., 34.4 ft., healed.
Scribed- 9" Fir N.60°W., 19.0 ft., "S 18 BT"
11" Fir S.76°W., 48.5 ft., "S 19 BT"

Fd. Ok by K. DeGroot - Oct. 2000 - M 136-1