

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7223)

-----  
Set quarter sec. post, from which a  
Pine 15" dia., bears N.85°W., 40 lks. dist.  
Pine 24" dia., bears S.85°E., 60 lks. dist.

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor - For: Oakland Placer Nickel and Chrome Mine - Nov. 17, 1886 (DCSO records Vol. 28 Page(s) 11811)

-----  
Intersect quarter post between secs. 17 and 18. Mkd. post No. (3) and claim No. (38). Set post by established witness trees, to wit:  
A pine 20" dia., bears S.85°E., 50 lks.  
A Pine 10" dia., bears N.85°W., 10 lks.  
Altitude 2353 ft.

Douglas Co. Surveyors Office - Arthur Boyer, D.C.S. - For: Freeport Sulphur Co. - Wit: Clyde Harrison; George Piper - Dec. 3, 1942

-----  
Found - One O.B.T., 16" Pine N.85°W., 23.4 ft. renewed scribe marks on bark.  
Marked new tree:  
A 20" Pine S.85°E., 33 ft.  
Drove a 4 x 4 post.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - May/June 1957 - C.S. File 42/269-1

-----  
Point for corner determined by O.B.T.  
Found - A 1" drill steel shaft & scribed wood post in mound of stone at corner point.  
I set an iron pipe with brass cap at point, in concrete, mkd. T30S R6W ¼ S S18 S17 2880, 1957.  
From which;  
A 16" Pine bears N.85°W., 21.7 ft., O.B.T., found scribe.  
A 27" Pine stump (logged) bears S.85°E., 31.5 ft., O.B.T., found scribe.  
An 11" Pine bears N.15°W., 50.0 ft. mkd. ¼ S18 BT.  
A 17" Pine bears S.19°E., 16.0 ft. mkd. ¼ S17 BT.  
Logging road bears West, 83.5 ft.

Fd. Ok 7/1964 DCSO C.S. File 53/40-59