

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec cor for 7, 8, 17 and 18

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7223-24)

Set post, cor. to secs. 7, 8, 17 and 18, from which
A Red Fir 12" dia., bears N.40°W., 175 lks. dist.
A Red Fir 6" dia., bears S.89°W., 185 lks. dist.
A Red Fir 4" dia., bears S.35°E., 51 lks. dist.
A Cedar 12" dia., bears N.45°E., 47 lks. dist.

Douglas Co. Surveyors Office - Arthur Boyer, D.C.S. - Wit:
George Pipe; Hilton Fogus; Al Weekley - Jan. 12, 1943 - C.S.
File 31/9

Found original Laurel BT and pile of rocks.
Cedar post at pile of rocks for center from which
A 16" Fir bears S.41½°W., 7.5 ft.
A 12" Fir bears N.78°W., 22.5 ft.
A 72" Fir (scribed on bark) bears N.53°E., 34 ft.
A 15" Madrone bears S.57°E., 17.0 ft.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - June/July 1957 - C.S. File 42/273-2

Location of corner determined by O.B.T.s:
60" Fir N.50°E., 34.0 ft., found scribe
15" Laurel snag, S.59°E., 16.5 ft., found scribe.
14" Fir S.41°30'W., 7.2 ft., found scribe.
At corner point, found 4" x 4" scribed wood post. I set an I.pipe with brass cap in concrete mkd: T30S R6W 7, 8, 17, 18, 2880, 1957, from which
6" Fir bears N.21°W., 25.2 ft. mkd. S7 R6W BT.
15" Cedar bears N.86°W., 32.0 ft. mkd. S18 R6W BT.
11" Fir bears S.33°W., 18.0 ft. mks. S18 BT.
12" Fir S.18°30'E., 43.6 ft. mkd. S17 BT.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Darby; Mike Stone - July 1964 - C.S. File 53/40-57

Found - D.Fir now 38" snag, N.40°W., 115.5 ft. previously opened. Good scribing visible "SR 6 W S6".
D.Fir now 48", N.84°W., 121.1 ft. (Not S.89°W) previously opened. Good scribing "BT" visible on old blaze.
D.Fir stump 22". previously opened, S.5°W., (Not S.35°E.) 33.7 ft. Good scribing visible "7 BT".
No trace found of orig. NE tree. Distances given in field notes check gov't notes, but bearings do not.
(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set Brass cap at cor. mkd: County Surveyors Office 1964

T 30 S R 6 W S 7 | S 8
S 18 | S 17

Trees recently mkd. for BTs by Cadastral Engineers:

23" I.Cedar S.53°W., 44.9 ft. mkd. T30S R6W S18 BT.

23" D.Fir S.55°E., 47.1 ft. mkd. T30S R6W S17 BT.

13" D.Fir N.33°E., 130.4 ft. mkd. T30S R6W S8 BT.

Wooden stake set by Cadastral Engineers for Temp. corner bears N.81°E., 2.9 ft.

Brass cap set by Markham for this same corner bears N.43°W., 36.3 ft.

BLM resurvey by Jelley & White under Group #s 350 & 551, Survey May 1963-July 1964 (DCSO recs. Vol.32 Pgs. 13584-85)

From the cor. of secs. , 8, 17 and 18, perpetuated and recorded by Godfrey in 1964, monumented with an I.P. 1" dia., 12" above the ground, firmly set with BC properly mkd.

from which the remaining original bearing trees:

A sawed Fir stump 24" dia., bears S.5°W., 51 lks. dist. with scribe marks 7 BT visible on opened blaze. (Rec. bearing S.35°E.)

A Fir 45" dia., bears N.83°W., 181 lks. dist., with illegible scribe marks visible on opened blaze. (Rec. bearing and distance, S.89°W., 185 lks.)

A dead Fir 43" dia., bears N.36½°W., 176½ lks. dist., with scribe marks S R6W S visible on opened blaze. (Rec. bearing and distance N.40°W., 175 lks.)

and new bearing trees:

A Fir 13" dia., bears N.34½°E., 197 lks. dist., mkd. T30S R6W S8 BT.

A Fir 23" dia., bears S.53°E., 72 lks. dist., mkd. T30S R6W S17 BT.

A Cedar 21" dia., bears S.53°W., 68 lks. dist., mkd. T30S R6W S18 BT.

Add marks BLM 1964 to bottom of brass cap.

From this point an I.Pipe 1" dia., 6" above ground, firmly set in concrete bears N.42°30'W., 0.545 chs. dist., with brass cap mkd. T30S R6W 7-8-17-18 2880 1957, from which bearing trees mkd. in 1943:

A Fir 60" dia., bears N.50°E., 51½ lks. dist., with scribe marks T30S R6W S8 CSBT visible on bark blaze.

A Madrone snag 15" dia., bears S.58°E., 24½ lks. dist, with scribe marks S17 T30S R6W CS BT visible on open double blaze.

A Fir 15" dia., bears S.44°W., 11½ lks. dist., with healed blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

and bearing trees marked in 1957:
A Fir 14" dia., bears S.17°E., 63½ lks. dist., with illegible scribe marks visible on partially healed double blaze.
A Fir 13" dia., bears S.33°W., 27½ lks. dist., with scribe marks 8S visible on partially healed blaze and BT visible on bark blaze at base.
A Cedar 18" dia., bears N.83½°W., 48 lks. dist., with scribe marks S18 R6W BT visible on partially healed double blaze.
A Fir 9" dia., bears N.21°W., 38½ lks. dist., with scribe marks S R6W BT visible on partially healed double blaze.

See BLM for a 1977 Administrative survey.

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0906, surveyed June/July 2009 - (DCS0 recs Vol. 56 Pg 22318 & Plat T30-6 2011)

The cor. of secs. 7, 8, 17 & 18, monumented with an iron post, 1¼" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd. from which the remains of orig. BTs
A sawed, decayed fir stump, 24" dia., bears S.5°W., 33.7 ft. with scribe marks BT visible on an opened blaze.
A fir snag, 47" dia., bears N.83°W., 119.5 ft. with no marks visible.
A fir snag, 38" dia., bears N.36½°W., 116.5 ft. with no marks visible.
and the remains of BTs mkd by Jelley & White
A fir, 30" dia., bears N.33¾°E., 130.0 ft. with a healed blaze. (Rec. N.34½°E.)
A fir, 21" dia., bears S.48¾°E., 58.4 ft. with a healed blaze. (Rec. S.53°E., 47.5 ft.)
A roothole bears S.53°W., 44.9 ft. alongside of which is a fallen cedar trunk, size indeterminate, with no marks visible.
From this cor. a point erroneously perpetuated as the cor. point by Boyer, Deputy Co. Surveyor, in 1943, and remonumented by Markham in 1957, bears N.42°28'58"W., (Rec. N.42°30'W.) 35.97 ft. monumented with an iron post, 1" dia., firmly set, projecting 3" above the ground, with brass cap mkd. T30S R6W 7 8 18 17 2880 1957 and is not utilized during the course of this survey, from which BTs mkd. by Boyer, reported by Jelley & White
A fir, 58" dia., bears N.50°E., 34.0 ft. with scribe marks 6 W BT visible on a bark blaze. continued next pg

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. cor. for 7, 8, 17 and 18

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A fir, 27" dia., bears S.48½°W., 7.6 ft. with no marks visible. (Rec. S.44°W.)
and the remains of BTs mkd by Markham, reported by Jelley & White
A sawed fir stump, 19" dia., bears S.17°E., 41.9 ft. with a partially healed blaze.
A decayed fir snag, 8" dia., bears S.33°W., 18.2 ft. with no marks visible.
A roothole bears N.83½°W., 31.7 ft. alongside of which is a fallen cedar trunk, 14" dia., with no marks visible.