

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 7 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7225)

-----  
Set quarter sec. post, from which a  
Fir 4" dia., bears N.40°E., 14 lks. dist.  
Fir 6" dia., bears S.75°W., 33 lks. dist.

John Markham, Jr. - For: Stomar Lbr. May 7, 1955 CS41/384-2

-----  
At the midpoint on sec. line, I set 3/4" x 36" I.P. for 1/4 sec. cor., from which  
10" Fir bears N.53°E., 10.5 ft. mkd. 1/4 S8 BT.  
12" W.Fir bears S.30°W., 9.0 ft. mkd. 1/4 S7 BT.  
Corner lies in small flat 120 ft. west of swamp.

BLM resurvey by Jelley & White under Group #s 551 & 350, Survey May 1963/July 1964 (DCSO recs. V. 32 Pgs 13586-87)

-----  
The 1/4 sec. cor. of secs. 7 and 8 determined at record bearing and distance from the original bearing trees:  
A Fir snag 30" dia., bears N.40°E., 14 lks. dist., with scribe marks 1/4 S visible on opened blaze.  
A large stump hole bears S.75°W., 33 lks. dist. with nothing remaining of the tree.

At the corner point  
Set an iron steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd:

1/4  
S 7 | S 8  
T 30 S R 6 W  
1963

from which new bearing trees:  
A White Fir 12" dia., bears N.80°E., 55 lks. dist. mkd. 1/4 S8 BT, on the overgrowth of a previous blaze.  
A yew 10" dia., bears N.29 1/2°W., 25 lks. dist., mkd. S7 BT.  
From this point, a point established by John H. Markham, Jr., in 1955, bears East, 0.42 chs. dist., monumented with an iron pipe, 1/2" dia., protruding 10" above ground, from which trees marked by Markham:  
A W.Fir 12" dia., bears N.55°E., 17 lks. dist., with a healed blaze. (Remarked 1/4 S8 BT, as described above.  
A down Fir 14" dia., bears S.33°W., 12 lks. dist., with a healed blaze.

Greg Lang - For: Rick Barnes - July 2005 - M148-10 & C.S. File 65/54-26D

-----  
Found - Brass Cap set by BLM and a dead yew tree to the NW per their 1963 renewal. continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 8" Pine bears S.8°E., 27.10 ft scribed "¼ S8 BT"  
7½" Fir bears S.57½°W., 21.40 ft scribed "¼ S7 BT"  
11" Fir bears N.71°W., 30.30 ft scribed "¼ S7 BT"  
24" Fir bears N.59¼°E., 73.20 ft scribed "¼ S8 BT"

Note- We set spikes in the base of all new BTs for measuring distances to the corner; bearings to the trees were measured with a total station & are based on the 1965 & 1982 BLM plats.

Corner lies in a small flat west of swamp.

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0906, surveyed June/July 2009 - (DCS0 recs Vol. 56 Pg 22318 & Plat T30-6 2011)

-----  
The ¼ sec. cor. of secs. 7 & 8, monumented with an iron post, 2½" dia., firmly set, projecting 4" dia., above the ground, with brass cap (properly) mkd from which the remains of an orig. BT

A roothole bears S.75°W., 21.8 ft. with no remains of the trunk visible.

and the remains of a BT mkd. by Jelley & White

A yew snag, 11" dia., bears N.29½°W., 16.5 ft. with no marks visible.

and BTs by Lang in 2005

A fir, 26" dia., N.59¼°E., 73.2 ft. with scribe marks ¼ S8 BT visible on a partially healed blaze.

A pine, 9" dia., S.7¼°E., 27.0 ft. with scribe marks ¼ S8 BT visible on a partially healed blaze.

A fir, 9" dia., S.57½°W., 21.4 ft. with scribe marks ¼ S7 BT visible on a partially healed blaze.

A fir, 12" dia., N.71¼°W., 30.3 ft. with scribe marks ¼ S7 BT visible on partially healed blaze.

Corner is located on a shallow NE slope, 30.0 ft. E of a graveled road, 16 ft. wide, bears S.15°E. & N.40°W.