

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7225)

-----  
Set post, cor. to secs. 5, 6, 7 and 8, from which a  
Fir 8" dia., bears N.20°E., 34 lks. dist.  
Fir 12" dia., bears S.80°E., 105 lks. dist.  
Fir 8" dia., bears S.45°W., 75 lks. dist.  
Cedar 40" dia., bears N.20°W., 20 lks. dist.

L.G. Hicks, approx. 1915 - C.S. File 19/28 & M 13-72

-----  
3" Cedar stake.  
Fir 8" N.20°E., 22.4 ft.  
Fir 12" S.80°E., 69.3 ft.  
Fir 8" S.45°W., 49.5 ft.  
Cedar 40" N.20°W., 13.2 ft.

BLM resurvey by Jelley & White, under Group #s 350 & 551, Survey May 1964/July 1964 (DCSO records, Vol. 32 Pg 13587-88)

-----  
The cor. of secs. 5, 6, 7 and 8, determined at record bearing and distance from the remaining original bearing tree:

A Fir 12" dia., bears S.45°W., 75 lks. dist., with scribe marks 30 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 30 S R 6 W

S 6 | S 5  
S 7 | S 8  
1963

from which new bearing trees

A sawed Fir stump 12" dia., bears N.85°E., 78 lks., mkd. T30S R6W S5 BT.

A cedar 8" dia., bears S.14°E., 35 lks. mkd. T30S R6W S8 BT

A Cedar 9" dia. bears S.51½°W., 23 lks. mkd. T30S R6W S7 BT

A Fir 10" dia., bears N.87°W., 112 lks. dist., mkd.

T30S R6W S6 BT.

From this point an iron pipe, ½" dia., 8" above ground, firmly set bears S.50°W., 0.31 chs. dist., established by persons unknown.

BLM resurvey by Jelley & Rogers, under Group #s 1024 & 1039 - Survey, April/Oct. 1980 (DCSO records, Vol. 42 Pgs. 16569-70)

-----  
The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground with 1963 brass cap.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the original bearing tree  
A Fir snag 12" dia., bears S.45°W., 75 lks. dist., with scribe marks 30 visible on opened blaze.  
and the remains of bearing trees mkd. by Jelley and White  
A Fir stump 15" dia., bears N.85°E., 78 lks. dist., with scribe marks 30S R6W S5 visible on opened blaze.  
A cedar 10" dia., bears S.14°E., 35 lks. dist., with scribe marks R6W S8 BT visible on open blaze.  
A Cedar 10" dia., bears S.51½°W., 23 lks. dist., with scribe marks 30S R6W S7 visible on open blaze.  
A Fir 12" dia., bears N.87°W., 112 lks. dist., with illegible scribe marks visible on partially healed blaze.  
and a new bearing tree  
A Cedar 5" dia., bears N.25°E., 34½ lks. dist. mkd. X BT.

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0906, surveyed June/July 2009 - (DCSO recs Vol. 56 Pg 22318 & Plat T30-6 2011)

-----  
The co. of secs. 5, 6, 7, & 8, monumented with an iron post, 2½" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd.  
from which the remains of an orig. BT  
A roothole bears S.45°W., 49.5 ft. alongside of which is a fallen, decayed fir trunk, 12" dia., with fragmentary scribe marks visible on an opened blaze.  
and the remains of BTs mkd by Jelley & White, reported by Jelley & Rogers  
A sawed fir stump, 15" dia., bears N.85°E., 51.5 ft. with scribe marks T30S R6W S5 BT visible on a partially healed blaze.  
A cedar, 13" dia., bears S.14°E., 22.0 ft., with a healed blaze. (Rec. 231.1 ft.)  
A cedar, 15" dia., bears S.51½°W., 15.2 ft. with a healed blaze.  
A fir, 23" dia., bears N.88¼°W., 73.9 ft. with a healed blaze. (Rec. N.87°W.)  
and a BT mkd by Jelley & Rogers  
A cedar, 13" dia bears N.25°E. 22.8 ft with a healed blaze  
From this cor. a point established by persons unknown bears S.50°36'37"W., 20.34 ft. monumented with an iron pipe, 1" dia., firmly set, projecting 6" above the ground, and is not utilized in the course of this survey.