

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7226)

Set quarter sec. post, from which a
W.Oak 24" dia., bears N.47°W., 90 lks. dist.
W.Oak 16" dia., bears N.35°E., 380 lks. dist.

Douglas Co. Surveyors Office - James W. Byron and crew - July 2, 1962 - C.S. File 49/139-92

Found - Old scribed stake, out of ground, and about 6 ft. west of corner. (See, also M 13-72)
Orig. 24" now 36" W.Oak N.47°W., 59.5 ft. We open and find faint scribing "BT"
Also find NE orig. BT, now down & partly rotted.
Set brass cap at cor. mkd.: County Surveyor's Office 1962
¼ S6 | S5 T30S R6W
New BTs -12" W.Oak bears N.60°W., 33.5 ft. scribed ¼ S6 CSBT
11" Cedar bears N.5°E., 32.0 ft. scribed ¼ S5 CSBT.

Fd. and used, 1980 BLM resurvey by Jelley & Rogers, (DCSO records, Vol. 42 Pg. 16571. Fd. B/C, 2 orig. BTs. and Byron's 2 BTs.