

PRIMARY CORNER DESCRIPTION No. Sec. cor. 5 & 6 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6460)

Set a post at proper distance cor. of secs. 5, 6, 31 and 32, from which:

- A R.Fir 30" dia., bears N.60°W., 11 lks. dist.
- A R.Fir 20" dia., bears S.40°W., 29 lks. dist.
- A R.Fir 24" dia., bears S.20°E., 22 lks. dist.
- A R.Fir 36" dia., bears N.25°E., 17 lks. dist.

GLO resurvey by Fred Mensch, under Contract #757 dated Sept. 14, 1904 (DCSO records, Vol. 15 Page 6502)

The corner of secs. 5 & 6 on the S. bdy. T29-6 being partially obliterated, I re-establish this corner in its original position, as follows:

Set a diorite stone 18 x 15 x 8 ins., 12" in the ground for cor. of secs. 5 and 6, mkd. with 5 notches on E. and 1 notch on W. edge; from which

- A W.Fir 10" dia., bears S.70°E., 28 lks. dist., mkd. T30S R6W S5 BT.
- A R.Fir 30" dia., bears S.40°W., 29 lks. dist., mkd. T30S R6W S6 BT.

L. G. Hicks - 1915 - C.S. File 19/28; M 13-72

Stone 18" x 15" x 8"
R.Fir 30", S.40°W., 19.1 ft.
W.Fir S.70°E., 18.5 ft.

BLM resurvey by Thielsen and White, under Group #'s 348 and 350 Surveyed July 1958/August 1959 (DCSO records, Vol. 30 Pages 12813-14)

The corner, monumented with an unmarked stone, 18x15x8 ins., set 6" in the ground, from which trees marked by Mensch in 1904:

- A Fir 12" dia., bears S.70°E., 28 lks. dist. mkd. T30S R6W S5 BT on open blaze.
- A Fir 36" dia., bears S.43°W., 29 lks. dist., mkd. with a healed blaze. (Rec. S.40°W.)

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION No. Sec. Cor. 5 & 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 29 S
S 31
S 6 | S 5
T 30 S R 6 W
1958

from which new bearing trees
A Fir 16" dia., bears S.43 3/4°E., 102 lks. dist., mkd.
T30S R6W S5 BT.
A Fir 23" dia., bears S.23°W., 95 lks. dist., mkd.
T30S R6W S6 BT.
Bury original corner stone alongside the iron post.

BLM resurvey by Jelley and Rogers, under Group #'s 1024 and 1039, Surveyed April/Oct. 1980 (DCSO records, Vol. 42 Pages 16566-67)

The sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with 1958 brass cap.
from which the remains of bearing trees mkd. by Mensch:
A root hole bears S.43°W., 29 lks. with a down fir alongside 34" dia., with healed blaze.
and the remains of bearing trees mkd. by Thielsen and White
A Fir snag, 18" dia, bears S.43 3/4°E., 102 lks. dist. with fragmentary scribe marks visible on partially healed blaze.
A Fir 28" dia., bears S.23°W., 95 lks. with healed blaze.
and a bearing tree of which I have no record:
A Fir 48" dia., bears N.53°W., 12 lks. with healed blaze.
and a new bearing tree:
A Fir 12" dia., bears S.78½°E., 56 lks. dist., mkd.
T30S R6W S5 BT.

BLM resurvey by Wayne Rogers under Group #1030, surveyed Aug/Sept 1980 (DCSO records Vol. 45 Page(s) 17254)

The cor. of 5 & 6 only, monumented with an iron post, 2½" dia., firmly set projecting 10" above ground with properly marked 1958 brass cap
from which the remains of the bearing trees mkd. by Mensch
A root hole bears S.43°W., 29 lks. dist., with a down fir, 34" dia., alongside, with healed blaze.
and bearing trees mkd. by Thielsen and White
A fir snag 18" dia., bears S.43 3/4°E., 102 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
A fir 28" dia., bears S.23°W., 95 lks. with healed blaze.
and a bearing tree of no record (Cont. Next Page)

PRIMARY CORNER DESCRIPTION No. Sec. cor. 5 & 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 48" dia., bears N.53°W., 12 lks. dist., with healed
blaze.
and a bearing tree mkd. by Jelley and Rogers
A grand fir 12" dia., bears S.78½°E., 56 lks. dist. with
scribe marks T30S R6W S5 BT visible on open blaze.

Howard Johnstone - For: Roseburg Forest Products - Jan. 23,
1990 - C.S. File 63/104-6

Found - 1958 Cadastral iron pipe with brass cap.
48" Fir N.53°W., 7.9 ft. low stump. No record
18" Fir S.43 3/4°E., 67.3 ft. snag, down. (1958)
12" G.Fir S.78½°E., 37.0 ft., high stump & pushed
over. (1980)
28" Fir S.23°W., 62.7 ft., high stump, healed face.
34" Fir S.43¼°W., 19.1 ft. windfall, scar visible,
logs cut. (1905)
New BT - 16" W.Fir N.61°W., 65.0 ft. scribed "T29S R6W S31 BT"
7" D.Fir S.70°W., 56.2 ft. scribed "T30S R6W S6 BT".
Corner lies in NW corner of 1989-90 clear cut unit about 100
ft. South of road.

DCSO-GIS Corner visitation - 8/10/2004 - Typed: 2/9/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK