

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 220620

PRIMARY CORNER DESCRIPTION SW 1/16 Sec. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Jelley & Rogers, under Group #s 1024 & 1039, Survey April/Oct. 1980 (DCSO records, Vol. 42 Pg. 16577)

Point for the SW1/16 sec. cor. of sec. 5, at intersection with the E & W center line of the SW¼ of Sec. 5.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: SW 1/16 S 5
1980

from which

A fir, 7" dia., bears S.22°E., 16½ lks., mkd: SW 1/16 S5
BT.

A fir, 14" dia., bears S.54°W., 29 lks., mkd: SW 1/16 S5
BT.

Douglas Co. Surveyors Office - Stephen J. Flauser - Mike Koch
- June 12, 2013 - C.S. File 67/38-29

Condition report only

Found - Monument fd as originally described but buried under remnants of fallen rotted log.
BTs fd as described we re-nail tags and flag trees. monument is uncovered, flagged and now protrudes 2" above ground.

Note - Monument is in SE corner of 10+ year old clear cut in mixed fir forest. Monument is near bottom of and on South edge of Westerly running draw.

Compass decl. 15½°E.