

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 32; & 5 of T31-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7194)

-----  
Set quarter sec. post, from which  
B.Oak 16" dia., bears S.21°W., 50 lks.  
Laurel 7" dia., bears N.4°E., 71 lks.

BLM resurvey by James Jelley under Group #585 - Surveyed July/Aug 1965 (DCSO records, Vol. 33 Page 13812)

-----  
The Corner perpetuated with an iron pipe 3/4" dia., firmly set, extending 18" above ground, from which the remains of the original bearing trees

The rotted remains of a Madrone stump 16" dia., bears N.4°E., 71 lks. with no marks remaining.

The stump hole of an Oak bears S.24°W., 50 lks. (Rec. S.21°W.)

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 6 W  
¼ S 32  
S 5  
T 31 S  
1965

from which new bearing trees

A Fir 6" dia., bears N.2½°W., 19 lks. dist., mkd. ¼ S32 BT.

A Madrone 40" dia., bears S.52°W., 91 lks. dist. mkd. ¼ S5 BT.

Deposit iron pipe alongside the iron post.