

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 240440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 17

Alias <u>906080</u>	Description <u>Cor #4 M S #307</u>
Alias <u>907010</u>	Description <u>Cor #4 M S #137</u>
Alias <u>908020</u>	Description <u>Cor #3 M S #138</u>
Alias _____	Description _____

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor - For:
Excelsior Mining District - Nov. 16, 1886 (DCSO records Vol.
28 Page(s) 11818)

Set post No. 3; from which
A Cedar 24" dia., bears S.59°E., 10 lks. dist.
A Fir 10" dia., bears S.63°W., 26 lks. dist.

Arthur Boyer, D.C.S. - Wit: Geo. Piper; Hilton Fogus; Al
Weekley -Jan. 15, 1943 - C.S. File 31/9

A 4 x 4 Fir post and pile of rock, from which
A 30" Fir bears N.21°W., 28.5 ft.
A 20" Pine bears S.77°E., 7.0 ft.
Marked ¼ S17 T30S R6W C.S.B.T.
Set by intersecting both mid section lines.

John H. Markham, Jr. - For: Hanna Cole & Ore. - May 23-June
13, 1957 - C.S. File 42/269-6

Location of corner determined by O.B.T.,
a 26" Pine stump, logged, bears S.77°E., 7.0 ft.
A 24" Fir stump, logged, bears N.21°W., 28.5 ft. Fd.scribe
At corner point found scribed post in large mound of stone.
I set an Iron pipe with brass cap in concrete mkd: T30S R6W
¼ S17 Center 2880 1957, from which
A 16" Fir bears S.3°E., 197.0 ft. mkd. ¼ S C.C. S17 BT
A 10" Fir bears N.50°E., 239.0 ft. mkd. ¼ S17 C.C. BT
Mining road bears West 112.0 ft. This corner lies in mining
area.