

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 8 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7224)

Set quarter sec. post, from which
A Pine 14" dia., bears N .80°E., 45 lks. dist.
A Pine 10" dia., bears S.40°E., 20 lks. dist.

Douglas Co. Surveyors Office - Arthur Boyer, D.C.S. - Wit: George Piper; Hilton Fogus; Al Weekley - Jan. 14, 1943 - C.S. File 31/9

Set between NW corner and NE corner midway.
Set pile of rock and Cedar Post, from which
A 20" Fir bears N.48°W., 42.5 ft. (on slope)
A 15" Fir bears S.60°W., 61.0 ft.
Note: Found a corner with 2 BTs scribed, probably with knife, on bark about 30 ft. N. and 45 ft. W. of corner as set. These trees probably refer to mining claim corner, did not disturb it.

John H. Markham, Jr. - For: Hanna Coal & Ore Co. - June/July 1957 - C.S. File 42/273-1

Location of corner determined by O.B.T.s:
30" Fir bears N.52°W., 39.0 ft., found scribe.
20" Fir bears S.61°W., 61.0 ft., found scribe.
At corner point, found 4 x 4 wood post scribed. I set an Iron pipe with brass cap in concrete mkd: ¼ S T30S R6W S8 S17 2880 1957, from which
10" Fir bears S.68°W., 30.3 ft. mkd. ¼ S 17 BT.
10" Cedar bears S.17°30'W., 32.2 ft. mkd. ¼ S17 BT.
7" Cedar bears S.80°E., 27.4 ft. mkd. ¼ S17 BT.
12" Fir bears N.34°E., 48.6 ft. mkd. ¼ S8 BT.
Corner lies on steep north slope. Road bears South 1010 ft. on top of mountain.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Wm. Stoffel; Mike Darby; Mike Stone - July 1964 - C.S. 53/40-56

Found - D.Fir stump (not Pine), now 30" dia., S.50°E., 19.8 ft. Old scribing found "BT". Ring count 100 years (notes call for 10" Pine S.40°E., 13.2 ft.)
D.Fir snag (not Pine) N.70°E., 29.7 ft. Old scribing visible "¼ S" (Notes call for 14" Pine N.80°E., 29.7ft.)
(Cont. Next Page)

