TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7216)

Set quarter sec. post, from which a
Laurel 8" dia., bers S.20°W., 187 lks. dist.
Cedar 14" dia., bears S.5°E., 103. lks. dist.

Douglas Co. Surveyors Office - James Bryon, Deputy - Jim Halterman; Mike Darby -Nov./Dec. 1963- C.S. File 53/40-30

Found - Orig. 8" now 24" Laurel S.20°W., 123.4 ft. Open & find good reverse scribing "BT".
Orig. SE BT. not found.
Set brass cap at cor. mkd: County Surveyors Office, 1963
¼ S20|S21 T30S R6W
New BTs -14" Red Fir bears S.73°E., 44.8 ft. scribed ¼ S21 CS BT.
10" Cedar bears S.71°W., 55.5 ft. scribed ¼ S20 CSBT
Small steam bears South, 125 ft. more or less, from corner.

Found OK Oct. 1998 by G. Nygren - M129-23

Ron Quimby - For: Guy Kennerly - 4/2008 - M146-73

Found - DCSO brass cap (per 1971 ren)
26" Madrone S.20°W., 123.4'
28" R.Fir stump, S.73°E., 44.8'
20" Cedar stump S.71°W., 55.5'
New - 14" Cedar S.69°E., 23.6'
7" Cedar N.74°E., 13.9'
16" Cedar S.32°W., 72.1'
New BTs scribed "¼ S BT"