

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias <u>908040</u>	Description <u>Cor #1, M S #138</u>
Alias <u>909010</u>	Description <u>Cor #1, M S #306</u>
Alias <u> </u>	Description <u> </u>
Alias <u> </u>	Description <u> </u>

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7216)

Set post, cor. to secs. 16, 17, 20 and 21, from which
A Pine 10" dia., bears S.20°W., 115 lks. dist.
A Pine 15" dia., bears S.25°E., 260 lks. dist.
A Pine 30" dia., bears N.40°E., 164 lks. dist.
A Pine 24" dia., bears N.45°W., 171 lks. dist.

Survey #138 - Noumeite Placer Nickel & Chrome Mine - For: Edson Adams & Harvey S. Brown - By: W.F. Briggs, U.S. Deputy Mineral Surveyor - Nov. 17, 1886 - DCSO records, Vol. 28 Page 11817

Beginning at a post mkd. No. 1 and claim 37 with a scribe, it also being the cor. post to secs. 16, 17, 20 and 21, being put in place by established witness trees of the govt. survey:
A Y.Pine 15" dia., bears S.25°E., 260 lks. dist.
A Y.Pine 20" dia., bears S.20°W., 115 lks. dist.
A Y.Pine 30" dia., bears N.40°E., 164 lks. dist.
A Y.Pine 24" dia., bears N.45°W., 171 lks. dist.
Also a high point of mountain, known as Terrerium Peak, bears S.56°E., distant about 6 miles.
Also a high point, know as Silver Peak bears S.23°E., distant about 5 miles.

Survey #306 of the Riddle Nickel Mining Claim - By: W.F. Briggs, U.S. Deputy Mineral Surveyor - Nov. 2-4, 1895 (DCSO records Vol. 28 Pgs. 11853; 11857)

Beginning at the southeast corner of sec. 17, identical with old location corner.
Set post, 4½ ft. long, 4" sq., 12" in the ground, in mound of stone, mkd. No 1 M.S. 306, corner No. 1, NE. corner of claim; from which
A Pine 24" dia., bears S.13°W., 30 lks. dist. mkd. No. 1 M.S. 306 BT.
A Pine 8" dia., bears S.78°E., 97 lks. dist. mkd. No. 1 M.S. 306 BT.
Tellurium Peak bears S.56°E., about 6 miles distant.
Silver Peak, bears S.23°E., about 12 miles distant.

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias 908040 Description Cor #1, M S #138

Alias 909010 Description Cor #1, M S #306

Alias _____ Description _____

Alias _____ Description _____

Arthur Boyer, DCS - For: Freeport Sulphur Co. - Wit: George Piper; Carl Gilbreath - Nov. 10, 1942 - C.S. File 31/9

Found - Old stake scribed and a pile of rocks set up for corner from which found trees cut into and which scribed on bark of
30" Pine S.20°W., 23 ft. "S20 T30S R6W. This tree was already blazed but burned in blaze.
A 30" Pine which bears N.60°W., 37 ft. had been cut into and found scribe marks showing distinctly, marked (with scribe) this tree on bark "S17 T30S R6W CSBT"
A 30" Pine S.25°E., 125 ft. on 19° slope, blazed, marked this tree on bark "S20 T30S R6W CSBT"
Blazed and scribed:
A 16" Fir on N. side of road, N.42½°E., 50.5 ft. from corner, "S16 T30S R6W CSBT" on bark.
For corner, set railroad iron driven upright in rock pile and scribed 3" Fir on four sides.

John Markham, Jr. - For: Hanna Coal & Ore. - May 23-June 13, 1957 - C.S. File 42/269-2

Location of corner determined from O.B.T.s:
30" Pine N.70°30'W., 36.0 ft. found scribe.
36" Pine S.11°30'W., 22.2 ft. found scribe.
20" Fir N.42°E., 49.5 ft. found bark scribe.
At point for corner, set an Iron pipe with brass cap in concrete mkd: T30S R6W S16 S17 S20 S21, 2880, 1957, from which:
A 14" Pine bears N.21°E., 44.4 ft. mkd. S16 BT.
A 20" Pine bears N.47°W., 44.4 ft. mkd. S17 BT.
A 10" Fir bears S.56°30'W., 56.3 ft. mkd. S20 BT.
An 18" Pine bears S.61°E., 83.0 ft. mkd. S21 BT.
Road bears North 17.0 ft.

Fd. Ok 7/1964 DCS0 C.S. File 53/40-58& C.S. 53/40-59

Douglas Co. Surveyors Office - Randall Smith; Stephen Flauser; Terrie Franssen - May 7, 1991 - C.S. File 64/15-10

Found - A 2½" dia. brass cap on a 1½" O.D. I.Pipe, protruding 3" above ground. (by Markham)
Iron train rail protrudes 4" above ground bears S.8°E., 1.6 ft. (by Boyer)

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias <u>908040</u>	Description <u>Cor #1, MS #138</u>
Alias <u>909010</u>	Description <u>Cor #1, MS #306</u>
Alias _____	Description _____
Alias _____	Description _____

36" now 33" dia. 1½ ft. high Pine stump with a burnt face, no scribing visible bears S.11½°W., 22.2 ft. (agrees with record, first noted in 1957 - source unknown)

18" now 21" DBH Pine with a fully healed single blaze bears S.61°E., 81.7 ft. (Rec. S.61°E., 83.0 ft. dist. is a slope measurement.)

8" now 28" DBH J. Pine with a fully healed single blaze bears S.78°E., 64.0 ft. (agrees with record) (1890 mineral survey)

15" now 24" dia. fallen pine with an opened double blaze illegible scribing visible in upper blaze and "BT" found in lower blaze, evidence of roots bear S.25°E., 171.6 ft. (agrees with record) Orig. BT.

New BTs -10" DBH D.Fir double blazed and scribed "T30S R6W S21 CS BT" bears S.52 ¾°E., 9.6 ft.

19" DBH Ponderosa Pine double blazed & scribed T30S R6W S16 CS BT" bears N.9¼°E., 125.3 ft.

14" DBH I.Cedar double blazed & scribed "T30S R6W S17 CS BT" bears N.26½°W., 119.7 ft.

Found OK Oct. 1998 by G. Nygren - M129-23
Fd. Ok by K. DeGroot - Oct. 2000 - M 136-1