

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 16 and 17

Alias <u>906100</u>	Description <u>Cor #1 M S #307</u>
Alias <u>908010</u>	Description <u>Cor #4 M S #138</u>
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7217)

Set quarter sec. post, from which a
Cedar 24" dia., bears S.2°E., 130 lks. dist.
Pine 30" dia., bears S.5°W., 117 lks. dist.

Survey by W.F. Briggs, U.S. Deputy Mineral Surveyor For: Excelsior Mining District - Nov. 16, 1886 (DCSO records Vol. 28 Page(s) 11818)

Intersect at ¼ S. post between secs. 16 and 17. Marked post No. 4 and claim 37.
Set post by the established witness trees, to wit:
A Cedar 20" dia., bears S.3°30'E., 129 lks.
A Pine 20" dia., bears S.8°30'W., 105 lks. dist.

Arthur A. Boyer, DCS - For: Freeport Sulphur Co. - Dec. 3, 1942 - C.S. File 31/9

Found pile of rocks for corner and stump for O.B.T. to SW. Found O.B.T., S.2°E., 85.8 ft., renewed scribe marks on bark. Set 4 x 4 post and scribed new BT:
A 30" Pine N.57°W., 12 ft.

John Markham, Jr. - For: Hanna Coal & Ore. - May/June 1957 - C.S. File 42/269-3

Corner location determined by O.B.Ts:
A 33" Cedar bears S.4°30'E., 88.0 ft. found scribe.
A 26" Pine stump bears S.6°W., 77.0 ft.
A 30" Pine snag bears N.57°W., 12.0 ft. found scribe.
At corner point found scribed wood post in large pile of stones. I set an Iron pipe with brass cap in concrete at point for corner, mkd: T30S R6W ¼ S, S17 S16 2880, 1957 from which
20" Pine bears S.13°E., 19.4 ft. mkd. ¼ S16 BT.
12" Pine bears N.72°W., 33.4 ft. mkd. ¼ S17 BT
9" Pine bears N.83°E., 74.2 ft. mkd. ¼ S16 BT.
A road bears West, 346.0 ft.