

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7217-18)

Set quarter sec. post, from which
A Pine 18" dia., bears S.10°W., 338 lks. dist.
A Cedar 30" dia., bears N.20°E., 30 lks. dist.

John H. Markham, Jr. - For: Stomar Lumber Co. - May/July 1955
- C.S. File 42/18-1 & C.S. File 41/384-1

Determined by O.B.T.s
A 40" Cedar bears N.20°E., 19.8 ft., scribe showing.
A 50" Pine bears N.18°W., 121.0 ft., scribe showing.
At corner point Set a 1" x 30" steel shaft.
Road bears North, 115.0 ft.

BLM resurvey by Lynn Roseberry under Group #649, Survey Aug/Sept. 1967 (DCSO records, Vol. 35 Pg. 14349)

From the ¼ sec. cor., perpetuated and recorded by John H. Markham, in 1955, monumented with a steel shaft, 1¼" dia., protruding 12" above the ground, firmly set, from which the remaining original bearing trees:

A Cedar 45" dia., bears N.20°E., 30 lks. dist., with scribe marks BT visible on opened and weathered blaze. and a tree described by Markham:

A Pine 46" dia., bears N.17°W., 185 lks. dist., with scribe marks ¼ S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:

¼
S 8 | S 9
T 30 S R 6 W
1967

from which a new bearing tree:

A twin Fir 37" dia., bears N.31¼°E., 69 lks. dist.
mkd. ¼ S9 BT.

Reset the steel shaft alongside the iron post.

Greg Lang - For: Rick Barnes - July 2005 - M148-10 & C.S. File 65/54-26C

Found - Brass Cap set by BLM 46" Cedar bears N.20°E., 19.80' (original)

41" Fir bears N.31¼°E., 45.54' (BLM in 1967)

8" Cedar bears S.75°W., 31.40 ft scribed "¼ S8 BT"

8" Cedar bears S.21¼°W., 73.30 ft scribed "¼ S8 BT"

continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Note - 7" Fir bears S.23¼°E., 58.80 ft scribed "¼ S9 BT"
We set spikes in the base of all existing & new BTs
for measuring distances to the corner; bearings
to the trees were measured with a total station
& are based on the 1965 & 1982 BLM plats.
Corner lies on a West slope South of a dirt road.