

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7218)

Set post, cor. to secs. 4, 5, 8 and 9, around which a mound of stones was raised according to instructions.
No trees being convenient.

John H. Markham, Jr. For: Stomar Lumber - Wit: George Vaughn July 16, 1951 - C.S. File 40/277-7

Found - A Fir 35" dia., bears N.57°E., 245.0 ft., found scribe. O.B.T.
A Fir 37" dia., bears N.7°W., 57.0 ft. O.B.T.
At corner point found old rail fence corner, large stone and Set a 1" x 30" Iron pipe from which
9" Fir bears N.55°W., 64.0 ft. mkd. S5 BT.
50" Fir bears N.4°E., 44.0 ft. mkd. S4 T30S R6W BT.
18" Fir bears N.23°E., 78.0 ft. mkd. S4 BT.
Old fence corner lies in the North & East from corner. This cor lies in the N end of an opening just on the East side of the main ridge. (Italics added 8/14/2024 JC)

See C.S. File 53/40-28 for DCSO search for.

BLM resurvey by Lynn Roseberry, under Group #649, Survey, Aug/Sept. 1967 (DCSO records. Vol. 35 Pgs. 14349-50)

The sec. cor. monumented with the original mound of stone, now scattered, located at intersection of faces of four bearing trees of which I have no record:
A Fir 47" dia., bears N.2°E., 168 lks. dist., with scribe marks S4 visible on opened blaze.
A Fir 60" dia., bears S.5¼°E., 396 lks. dist., with a healed blaze.
A Fir 41" dia., bears S.69½°W., 330 lks. dist., with scribe marks T30S R6W S8 visible on opened blaze.
A sawed Fir stump 55" dia., bears N.2 3/4°W., 117 lks. dist., with scribe marks R6W visible on opened blaze.
A count of the growth rings on the three opened trees gives an average age for the blazes of 106 years.
At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd: T 30 S R 6 W
S 5 | S 4
S 8 | S 9
1967
No tree available to mark in sec. 5. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

From this point a locally established cor., bears N.6½°E., 0.81 chs. dist., perpetuated and recorded by Markham in 1951, the cor. is located at cor. of old rail fences extending N. and E.; monumented with an unmarked stone alongside of which is an iron pipe, 1" dia., protruding 10" above ground, firmly set, from which bearing trees mkd. by Markham:

A fir 55" dia., bears N.6 3/4°E., 70 lks. dist., mkd. T30S R6W S4 BT on bark blaze.

A Fir 25" dia., bears N.24½°E., 117 lks. dist., mkd. with a healed double blaze.

A Fir 18" dia., bears N.53°W., 98 lks. dist., mkd. with a healed blaze.

The corner falls in a rocky barren.

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0906, surveyed June/July 2009 - (DCS0 recs Vol. 56 Pg 22317 & Plat T30-6 2011)

The cor. of secs. 4, 5, 8, & 9, monumented with an iron post, 2½" dia., firmly set, projecting 2" above a mound of stone, 3½ ft. base, 1 ft. high, with brass cap (properly) mkd. from which the remains of bTs mkd by persons unknown by Roseberry

A sawed, decayed fir stump, 60" dia., bears N.2°E., 110.9 ft. with a healed blaze.

A sawed double fir stump, 62" dia., bears S.5¼°E., 261.4 ft. with a healed blaze.

A fir, 45" dia., bears S.69½°W., 217.8 ft. with scribe marks S S8 visible on an opened blaze.

A sawed, decayed fir stump, 54" dia., bears N.2¾°W., 77.2 ft. with a healed blaze.

and new BTs

A fir, 6" dia. bears N.68½°E., 35.0 ft mkd: T30S R6W S4 BT

A pine, 21" dia., bears S.41¾°E., 216.5 ft. mkd T30S R6W S9 BT.

A fir, 5" dia., bears N.31¼°W., 44.6 ft mkd T30S R6W S5 BT

From this cor. a point established by Markham in 1951, at the intersection of old rail fences no longer in existence, bears N.6°30'00"E., 53.46 ft. alongside of which is an iron pipe, 1" dia., lying loose of which is an iron pipe, 1" dia., lying loose on the ground, and is not utilized in the course of this survey, from which BTs mkd by Markham Jr.

A sawed fir stump, 65" dia., bears N.6¾°E., 46.2 ft. with a healed blaze.

A sawed fir stump, 34" dia., bears N.24½°E., 77.2 ft. with a healed blaze.

A fir, 31" dia., bears N.53°W., 64.7 ft. with a healed double blaze.

continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Corner is located 120 ft. E of a ridge top and a graveled road, 10 ft. wide, bears S.15°E. and N.25°W.