

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 311700

PRIMARY CORNER DESCRIPTION S. Sec. Cor. for 32 & 33 only, T29-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Fred Mensch, under Contract #757 dated Sept. 14, 1904 (DCSO records, Vol. 15 Page 6500)

Intersect S. bdy. of the Tp. 10.77 chs. S.89°54'E., of the cor. of secs. 4, 5, 32 and 33, which is a post greatly decayed, witnessed as described by the surveyor general. Set a limestone 15 x 8 x 6", 10" in the ground for closing corner of secs. 32 and 33, mkd. CC on N. with 4 grooves on E. and 2 grooves on W. face, from which

A W.Fir 12" dia., bears N.43°E., 31 lks. mkd. T29S R6W S33 BT.

A W.Fir 10" dia., bears N.83°W., 60 lks. dist., mkd. T29S R6W S32 BT.

I destroy marks on former corner and bearing trees referring to these sections.

John Markham, Jr. - For: Stomar Lumber Co. - Aug/Oct. 1956 - C.S. File 42/190-1

Point for corner determined by old BTs.

A 24" W.Fir bears N.43°E., 20.5 ft.

At corner point, Set a 1½" x 35" truck axle with flange up. from which

A 48" Fir bears N.80°E., 107.0 ft. bark scribed S32 BT.

A 20" Cedar bears S.30°W., 101.5 ft. mkd. S4 BT X.

Cor. lies in creek along East edge of old landing.

Sec. cor. to 5 and 4 is West, about 700 ft.

BLM resurvey by Thielsen and White, under Group #'s 348 and 350. Surveyed July 1958/Aug. 1959 - (DCSO records. Vol. 30 Page 12824)

(At 80.99 chs.) the orig. closing cor. of secs. 32 and 33, determined at record bearing and dist. from the remaining original bearing tree:

A Fir 25" dia., partially dead, bears N.43°E., 31 lks. mkd. S R6W S33 BT.

(At 81.20 chs.) Intersect the S. bdy. of the Tp.

Point for the closing corner of secs. 32 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd:

	C	C	
T 29	S	R 6	W
	S 32	S 33	
	S 4		
T 30	S	R 6	W
			1958

from which

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 311700

PRIMARY CORNER DESCRIPTION Sec. Cor. 32 & 33 only, T29-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears N.58°E., 146 lks. dist., mkd.
T29S R6W S33 CC BT.

A Cedar 10" dia., bears N.22½°W., 378 lks. dist., mkd.
T29S R6W S32 CC BT.

From this point, the cor. of secs. 4 & 5, T30S R6W, bears
N.89°24'W., 11.12 chs.

Doug. County Surveyors Office - A. Victor Cangie; Mike
Tompkins; Karen Cheney; Pete Earle - Nov. 18, 1976 - C.S.
File 59/26-16

Found - A 1½" axle with flange up at corner point.
From which:

An orig. 12" now 24" W.Fir, snag, bears N.43°E., 20.5 ft.
visible "29W S33 BT" on previously opened blaze.

A 48" now 49" Fir bears N.85°E., (Rec. N.80°E.) 97.0 ft.
(Rec. 107.0 ft.) Tree is alive and shows illegible bark
scribing.

A 20" now 24" freshly cut Cedar bears S.30°W., 101.5 ft.
Lower blaze previously opened but no scribing visible.
We open upper blaze and find "X" scribe.

New BTs -9" Fir bears S.6°W., 52.8 ft. mkd. "T30S R6W S4 CC
CS BT".

An 11" D.Fir bears N.51°E., 63.7 ft. mkd. "T29S R6W
S33 CC CS BT" in a double blaze.

An 11" D.Fir bears N.5°W., 59.5 ft. mkd. "CC T29S
R6W S32 CS BT" in a double blaze.

Note: In 1958, BLM ran South on the line between S32 and S33
and reported that the point referenced by the found
orig. BT, fell 21 lks. North of the South bdy. of T29S.
They reported setting a brass cap 21 lks. South of the
point and on line but it was not found. They also
scribed two trees:

A 10" Fir bearing N.58°E., 96.4 ft.

A 10" Cedar bearing N.22½°W., 248.8 ft.

We find the Cedar but not the Fir. We pull out the
recorded bearing and distance from the Cedar and miss
the reported corner point. (BLM's corner) The axle
bears N.35½°E., 27.3 ft. from point established from
BLM's Cedar bearing tree.

BLM resurvey by Jelley and Rogers, under Group #'s 1024 and
1039. Surveyed April/Oct. 1980 (DCSO records, Vol. 42 Pages
16562-63)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. 32 and 33 only, T29-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

True point for the closing cor. of secs. 32 and 33, from which the remaining bearing tree mkd. by Thielsen and White:

A Cedar 18" dia., bears N.24½°W., 394 lks. dist., with healed blaze. (Rec. N.22½°W., 378 lks.)

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 29 S R 6 W
C C
S 32 | S 33
T 30 S R 6 W
1980

from which new bearing trees

A Fir 8" dia., bears N.73½°E., 84 lks. dist., mkd. T29S R6W S33 CC BT.

A Fir 6" dia., bears N.49½°W., 57 lks. dist., mkd. T29S R6W S32 CC BT.

The NE BT and the I.P. set by Thielsen and White, in 1958-59, have been destroyed by logging activity.

From this point, the original closing corner of secs. 32 and 33, bears N.0°06'W., 0.38 chs. dist., perpetuated and recorded by John H. Markham, Jr. in 1956, and further perpetuated and recorded by A. Cangie in 1976, monumented with an axle, 1½" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree:

A Fir snag 24" dia., bears N.43°E., 31 lks. dist, with illegible scribe marks visible on bark.

and the remains of bearing trees mkd. by Markham

A Fir, 50" dia., bears N.85°E., 145 lks. dist., with illegible scribe marks visible on bark.

A sawed Cedar stump 24" dia., bears S.30°W., 154 lks. with scribe mark X visible on opened blaze.

and bearing trees mkd. by Cangie:

A Fir 16" dia., bears N.50°E., 97 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A Fir 11" dia., bears S.8¼°W., 81 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A Fir 12" dia., bears N.2½°W., 93 lks. dist., with illegible scribe marks visible on partially healed double blaze.

continued next page

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 311700

PRIMARY CORNER DESCRIPTION S. Sec. Cor. for 32 & 33 only, T29-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed April/June 2002, - (DCSO records Vol. 54 Page(s) 21131-2)

The closing cor. of secs. 32 & 33, on the S. bdy. of the tp. monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Jelley & Rogers

A fir, 13" dia., bears N.66½°E., 51.0 ft., with a healed blaze. (Record, N.73½° E., 55.4 ft.)

A fir snag, 9" dia., bears N.49½°W., 37.6 ft., with a healed blaze.

and a new bearing tree

A fir, 8" dia., bears N. 49¾°W., 48.0 ft., mkd. T29S R6W S32 CC BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

From this point, the orig. closing cor. of secs. 32 and 33, on the S. bdy. of the tp., bears N.0°11'35"W., 25.81 ft. (record, N.0°06'00"W., 25.08 ft.), monumented with an axle, 1½" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree

A decayed fir snag, 24" dia., bears N.37°E., 20.5 ft., with scribe marks 33 T visible on decayed face. (Record, N.43°E.)

and the remains of a BT mkd. by John H. Markham, Jr., in 1956, reported by Jelley & Rogers

A fir snag, 48" dia., bears S.86¼°E., 85.9 ft., with no marks visible. (Record, N.85°E., 95.7 ft.)

and a bearing tree mkd. by the Douglas County Surveyors Office, in 1976, reported by Jelley and Rogers

A fir, 17" dia., bears S.12°W., 56.6 ft., with a healed blaze. (Record, S. 8¼°W., 53.5 ft.)

Corner is located in swampy area.

The geographic position (NAD 1983 (CORS)) of the cor. established by Thielsen and White, as determined by NAVSTAR GPS, utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:

Latitude: 42°59'55.74"N. Longitude:123°25'27.05"W.

Fd. OK by D. Edwards, 3/2011 - M162-22