

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 33; & 4 of T31-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7193)

Set quarter sec. post, from which
W.Oak 26" dia., bears S.47°W., 57 lks.
B.Oak 19" dia., bears N.39°W., 125 lks.

Doug. County Surveyors Office - James Byron; Gomer Welker; J. Fee - Oct. 1956/Jan. 1957 - Drawer 48, Rd. #93 file.

Found - Orig. NW BT, now 26" W.Oak, checks bearing and distance to scribed 4x4 inch stake set for corner by R. Gee. BT opened by Gee "BT" scribing visible. (No record source found for Gee survey referred to by Byron)

The SW BT is gone.

Set Brass cap alongside post mkd. "¼ Section 33 T30S R6W
County Surveyors Office, 1956 4 T31S R6W"

From which:

24" R.Fir bears N.39°W., 58.3 ft. scribed "¼ S33
T30S R6W CS BT".

24" W.Oak bears N.60°E., 4.0 ft. scribed "¼ S33 CS
BT".

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/40-3

Found - Brass cap at corner and all BTs, except NW BT, now dead.

New BT - 6" R.Fir bears S.78°E., 28.0 ft. scribed "¼ S4 CSBT"
Fence corner bears S.53°W., 15.0 ft.

Fd. OK by K. DeGroot, Jan. 2004 - M137-77