

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7215)

Set quarter sec. post, from which a
Laurel 24" dia., bears N.70°W., 86 lks. dist.
B.Oak 17" dia., bears S.25°E., 68 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/40-31

Found - Orig. 17" now down, 24" B.Oak S.25°E., 45.5 ft. shows good scribing.
Find stump section of original NW bearing tree.
Set brass cap at cor. mkd: County Surveyors $\frac{1}{4}$ $\frac{S21}{S28}$ T30S R6W Office, 1963
New BTs - 15" R.Fir bears N.77°W., 31.5 ft. scribed $\frac{1}{4}$ S21 CS BT.
13" laurel bears S.43°W., 17.2 ft. scribed $\frac{1}{4}$ S28 CS BT.
Corner is under N-S fence and 30 ft. north of fence corner.

Douglas Co. Surveyors Office - John Powell - Frank Jones; W. Penley - Sept. 11, 1969 - C.S. File 53/40-109

Found - 1963 DCSO brass cap, firmly set.
13" Laurel S.43°W., 17.2 ft. scribe visible.
No trace of NW bearing tree.
New BT - 12" Laurel N.35°E., 13.5 ft. mkd. $\frac{1}{4}$ S21 CS BT.

Howard Johnstone - For: Roseburg Lumber - Sept. 26, 1989 M 109-2

Found - No monument - in cat trail.
12" Madrone, dead, with scribe visible, bears N.35°E., 13.5 ft.
16" Madrone with healed blaze, bears S.43°W., 17.2 ft.
New BT - 19" Madrone bears S.80°E., 66.0 ft.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 3/31/1998 - C.S. File 66/2-9

Found - No monument - Corners falls in cat trail.
12" now 12" dia., down and rotting Madrone, scribing visible on unhealed double blaze, " $\frac{1}{4}$ S21 CS BT". A cluster of small Madrones found near record "N..35°E., 13.5 ft." 1969
(Cont. next page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

13" now 19" dia., Madrone with a partially healed rotted double blaze, no scribing visible, bears S.43°W., 17.2 ft. (Agrees with rec.) 1963
19" now 19" dia., Madrone with an unhealed single blaze, scribing visible "¼ S BT", a nail with brass washer mkd: "RLS 498" set in blaze, root crown bears S.83½°E., 66.0 ft. (Rec. S.80°E., 66.0 ft.) 1989
Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" iron pipe is set at a position determined from by found BTs. Protrudes 5" above ground, stamped: DOUGLAS COUNTY SURVEYOR'S OFFICE
T30S R6W
S21
S28
1998
6" dia., Madrone, double blazed and scribed "¼ S21 CS BT" bears N.34°E., 12.1 ft.
18" dia., W.Oak, double blazed and scribed "¼ S21 CS BT" bears N.19°W., 77.1 ft.
Corner lies in old cat road.

Found OK by K. DeGroot, Oct. 1999 - M133-37
Found OK by K. DeGroot, Dec. 2000 - LP 2000-0092 A&B
Fd. Ok by R. Quimby, 4/2008 M146-73