

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. For Secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7217)

Set quarter sec. post, from which
A Pine 14" dia., bears S.25°W., 30 lks. dist.
A Pine 6" dia., bears N.75°W., 98 lks. dist.

BLM resurvey by Lynn Roseberry under Group #649, Survey Aug/Sept 1967 (DCSO records, Vol. 35 Pgs. 14348/49)

The ¼ sec. cor., determined at record bearing from the original bearing trees:

A shattered Pine 23" dia., bears N.75°W., 38 lks. dist., with scribe marks ¼ S visible on opened blaze. (Rec. distance, 98 lks.)

A Pine snag 33" dia., bears S.25°W., 30 lks. dist., with scribe marks ¼ S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 30 S R 6 W

¼ $\frac{S\ 9}{S\ 16}$
1967

from which new bearing trees

A Pine 23" dia., bears N.13¼°W., 127 lks. dist., mkd. ¼ S9 BT.

A Fir 11" dia., bears S.79°W., 22½ lks. dist., mkd. ¼ S16 BT.