

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7209)

Set quarter post, from which
W.Oak 24" dia., bears S.48°W., 75 lks. dist.
W.Oak 20" dia., bears N.78°E., 167 lks. dist.

John H. Markhman, Jr. - For: Harry Dayton - Oct. 16, 1952
C.S. File 41/78-1

Determined by O.B.Ts:
A W.Oak stump 30" dia., bears S.48°W., 49.5 ft. - found old face.
At Corner point I set 1" x 30" truck axle, from which
A W.Oak 30" dia., bears N.36°E., 60.5 ft. mkd. ¼ S, S34 BT
An Ash 13" dia., bears S.73°W., 51.0 ft. mkd. ¼ S S33 BT.
Fence corner at County Road bears S.6°W., 160.5 ft.
Added 6/20/2024 - DCSO JC
The corner pt. was first determined by description on page 52, volume 54 Douglas County Deed records.
I fd. BT described therein.