TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7211)

Set quarter sec. post from which
B.Oak 5" dia., bears N.89°E., 22 lks. dist.
B.Oak 10" dia., bears S.20°W., 88 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Nov/Dec. 1963 - C.S. File 53/40-7

Found - Orig. 5" now 8" B.Oak, we open and find good reverse scribing.
Orig. SW BT not found.
Set brass cap at cor. mkd: County Surveyors Office, 1963
¼ S21|S22 T30S R6W
New BTs - 8" R.Fir bears S.26°W., 11.2 ft. scribed ¼ S21 CS BT.
14" R.Fir bears S.20°E., 26.0 ft. scribed ¼ S21 CS BT.
Fence to North and East.

Howard Johnstone, L.S. #498 - Sept. 26, 1989 - M 109-2

Found - 1963 County Brass cap/Iron pipe.
14" Fir snag bears S.20°E., 26.0 ft.
8" Fir down, bears S.26°W., 11.2 ft.
New BTs -12" Madrone bears East, 20.0 ft.
12" Cedar bears N.45°E., 49.8 ft.

Found OK Oct. 1998 by G. Nygren - M129-23
Fd. Ok by Greg Lang 9/2007 - M154-46