

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7211)

Set post cor. to secs. 15, 16, 21 and 22, from which

- A B.Oak 6" dia., bears N.57°E., 62 lks. dist.
- A W.Oak 13" dia., bears S.20°E., 115 lks. dist.
- A B.Oak 6" dia., bears S.28°W., 183 lks. dist.
- A B.Oak 10" dia., bears N.40°W., 83 lks. dist.

John H. Markham, Jr. - For: Stomar Lumber Co. - May 9 and July 2, 1955 - C.S. File 42/18-2

Determined by O.B.T.

At Corner point, Set a 1" x 30" I.Pipe from which

- 24" Ash bears East, 18.7 ft. - O.B.T., found scribe.
- 7" W.Oak bears N.34°W., 12.0 ft. mkd. S16 BT.
- 5" W.Oak bears S.24°W., 14.5 ft. mkd. S22 BT.
- 8" W.Oak bears S.10°E., 15.0 ft. mkd. S22 BT.

Jerry Creek bears East 23.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby & Jim Halterman - Dec. 1963/Jan. 1964 - C.S. 53/40-10

Found - Pipe at corner and all BTs as recorded by Markham.

New BT - 14" R.Fir bears N.59°E., 30.9 ft. scribed S15 T30S R6W CS BT.

Douglas Co. Surveyors Office - John M. Powell; Willie Penley; J. Heritage - Dec. 8, 1970 - C.S. File 53/40-103

Found - Scribing for renewal BTs. Destroyed and Iron Pipe removed. The Ash used by J.H. Markham to locate the sec. cor. was not of record. It does show old axe work and very old scribe marks.

Orig. 6" now 12" B.Oak S.28°W., 120.9 ft., opened for scribe "21"

No trace of other original BTs.

The B.Oak used on this date to monument the corner checks record in all respects. Also, tie from old Nickel Mountain Road traverse checks within a few feet of present corner location.

Tie from Brass cap to Iron pipe by Markham: S.11°E., 84.4 ft. Set Brass cap at cor. mkd: County Surveyors T30S R6W

Office	S16	S15
1970	S21	S22

New BTs - 7" W.Oak N.9°W., 55.0 ft. scribed "T30S R6W S16 CS BT"

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

19" W.Oak N.42°E., 36.5 ft. scribed "T30S R6W S15
CS BT"

10" W.Oak S.77½°W., 12.7 ft. scribed "T30S R6W
S21 CS BT"

8" B.Oak S.70°E., 21.0 ft. scribed "T30S R6W S22
CS BT"