

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7212-13)

-----  
Set post cor. to secs. 9, 10, 3 and 4, from which  
A Yew 3" dia., bears S.80°E., 17 lks. dist.  
A Red Fir 12" dia., bears N.78°E., 16 lks. dist.  
A Dogwood 2" dia., bears N.20°W., 15 lks. dist.  
A Red Fir 12" dia., bears S.80°W., 80 lks. dist.

BLM Resurvey by Lynn Roseberry under Group #649, Survey Aug/Sept. 1967 (DCSO records Vol.35 Pg. 14345)

-----  
Point for the cor. of secs. 3, 4, 9 and 10 at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 6 W  
S 4 S 3  
S 9 S 10  
1967

from which

- A Fir 26" dia., bears N.13½°E., 67½ lks. dist., mkd.  
T30S R6W S3 BT.
- A Fir 53" dia., bears S.82°E., 121 lks. dist., mkd.  
T30S R6W S10 BT.
- A W.Fir 4" di., bears S.11 3/4°W., 21 lks. dist. mkd.  
X at breast height and BT at base.
- A W.Fir 13" dia., bears N.65¼°W., 130 lks. dist., mkd.  
T30S R6W S4 BT.

An iron pipe of which I have no record, 1" dia., protruding 12" above the ground, firmly set, bears S.31 3/4°E., 55 lks. dist.