

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page(s) 7213)

Set quarter sec. post from which a
 Dogwood 3" dia., bears S.32°W., 18 lks. dist.
 Cedar 4" dia., bears N.25°E., 7 lks. dist.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: George & Dennis Vaughn - March 8, 1952 - C.S. File 40/386-6

Determined from O.B.T.
 A Fir 24" dia., bears S.66°E., 8.0 ft., found scribed and remarked.
 A Laurel 24" dia., bears South, 13.7 ft. O.B.T., I remarked.
 At corner point I set 1" x 30" I.Pipe from which
 A Fir 10" dia., bears N.43°W., 24.0 ft. mkd. ¼ S4 BT.
 Creek bears North, 35.0 ft. Twp. line bears North 2395.0 ft.

BLM resurvey by Lynn Roseberry under Group #649, survey - Aug/Sept. 1967 (DCSO records, Vol.35 Pgs. 14346-47)

The ¼ sec. cor. perpetuated and recorded by Markham in 1952, from bearing trees of which I have no record, monumented with an 1" iron pipe, protruding 8" above the ground, firmly set. This corner is accepted as the best available evidence of the position of the original corner.
 from which bearing trees reported by Markham:
 A Fir 25" dia., bears S.62½°E., 13 lks. dist., with no scribe marks visible on opened blaze. This tree remarked ¼ S BT on the bark by Markham.
 A dead Madrone 25" dia., bears S.1¼°W., 22½ lks. dist., with no scribe marks visible on opened blaze.
 and a bearing tree mkd. by Markham in 1952:
 A shattered Fir 10" dia., bears N.40½°W., 36 lks. dist. with scribe marks ¼ S4 visible on open blaze.

At the corner point
 Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the local iron pipe, with brass cap mkd

¼
 S 4 | S 3
 T 30 S R 6 W
 1967

from which a new bearing tree
 A Fir 30" dia., bears N.85°E., 15 lks. dist., mkd.
 ¼ S4 BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19212)

The ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with a 1967 brass cap properly mkd. from which the remains of bearing trees recorded by John Markham, Jr., in 1952

A fir, 28 ins. diam., bears S. 62½° E., 13 lks. dist., with rotted blaze.

A madrone stump, 25 ins. diam., bears S. 1¼° W., 22½ lks. dist., no visible marks.

and the remains of a bearing tree mkd. by Markham

A root crown, 14 ins. diam., bears N. 40½° W., 36 lks. dist., no visible marks.

and the remains of a bearing tree mkd. by Roseberry

A fir snag, 24 ins. diam., bears West, 15 lks. dist., with scribe marks S4 BT visible on partially healed blaze. (Record, N. 85° E.)

and a new bearing tree

A fir, 12 ins. diam., bears N. 52° W., 8½ lks. dist., mkd. ¼ S4 BT.