TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7212)

Set quarter sec. post from which
A Red Fir 10" dia., bears N.20°W., 132 lks. dist.
A Pine 24" dia., bears S.85°E., 460 lks. dist.

BLM resurvey by Lynn Roseberry, under Group #649 - Aug/Sept. 1967 DCSO records Vol. 35 Pg. 14343)

Point for the ¼ sec. cor. of secs. 10 and 15 at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 30 S R 6 W
¼ S 10
S 15
1967

from which
A Fir 31" dia., bears N.80 3/4°E., 71 lks. dist., mkd. ¼ S10 BT.
A Fir 35" dia., bears S.44°W., 40 lks. dist., mkd. ¼ S15 BT.

Fd. Ok by K. DeGroot, 12/2005, M146-32

David Edwards - For: Nickel Mountain LLC - 11/2021 - M180-70

Found - Brass cap
The Fir N.80¾°E., is gone.
36" Fir snag w/healed blaze bears S.44°W., 26.4'
A steel post is 0.5' east.