

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7203)

Set quarter sec. post from which
W.Oak 14" dia., bears S.60°E., 314 lks. dist.
W.Oak 12" dia., bears N.81°W., 658 lks. dist.

F. C. Frear - Witnesses: H.A. Rasor; J.B. Henslee - April 15, 1919 - Field Book 46 Page 45

Reset from 20" W.Oak BT stump which bears S.60°E., 3.14 chs. Marks plain.
I set a 3/4" x 48" Iron bolt and a 10" x 12" x 12" sandstone, from which
A 4" Prune tree bears N.45½°E., 75½ lks., C.S.B.T.

George Grubb - For: Ralph Huffman - March 1980 - M 79-34

Set Brass cap.
BTs - 20" Pine bears S.28°W., 46.9 ft. scribed ¼ S34 BT on a double face.
26" Cottonwood bears S.36°E., 68.1 ft. scribed ¼ S35 BT on a double face.

Fd. OK - Russ Dodge - Jan. 1997 - 1997-0020
Fd. Ok by R. Brown, 9/1998 - M129-13
Fd. BC in Rd 1' deep, 4/2013 - D. Edwards, M165-32