

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 27, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7204)

Set post, cor. to secs. 22, 23, 26, & 27, around which a mound was raised as per instructions.

Greg Lang - For: Merl Wright - 9/2007 - C.S. File 65/60-41B & M154-46

Found - Original was set by Addison Flint in 1855. Original corner was a raised mound with no recorded BTs. I looked for the original corner and did not find it.
Set - Using the double proportion method, I set a 5/8" x 36" iron rod with plastic cap marked "Lang Surveying". A Steel post with red paint is set beside the corner.
5/8" x 30" iron rod with plastic cap marked "Lang Surveying" bears S.88°45'00"E., 40.03'.
5/8" x 30" iron rod with plastic cap marked "Lang Surveying" bears S.13°41'00"W., 32.52'
A 5/8" x 30" iron rod property corner with plastic cap marked "Lang Surveying" bears N.1°55'30"E 162.20'
A 5/8" iron rod property corner bears S.87°23'23"W., 247.08'
Note - Corner is located on the south side of the railroad tracks as they travel southwest from Riddle.

Fd as per 2007 ren (damaged YPC) by C Sweeden, 3/2015, M169-11 & M169-75