

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6433)

-----  
Set a post for 1/4 sec. cor, from which,  
A B. Oak, 18" dia., bears S.65°W., 26 lks.  
A B. Oak, 15" dia., bears S.40°E., 15 lks.

John H. Markham, Jr., - Witnesses - J.A. Cross , G.S. Ausmus  
- Mar. 7, 1952 - C.S. File 40/386-5

-----  
Determined by O.B.T.  
A 22" B.O. bears S.55°W., 17.2'  
A 15" B.O. bears S.35°E., 9.9'  
At corner point set 1"x30" I.P. from which,  
A La. 9" in dia. bears N.45°E., 32.4' dist., mkd. 1/4 S,  
Sec. 23  
A W.O. 20" dia., bears S.45°W., 71.5' dist., mkd. 1/4 S,  
Sec. 22 2880, BT  
There is a fence running N-S-E from corner.

Doug. County Surveyors Office - James W. Byron, Co. Surveyor  
- J. Powell & Crew - For: Co. Rd. & Sproul - 12/12/68 - C.S.  
File 54/74

-----  
Found - 1" Iron pipe at 1/4 corner, no trace of old Orig. BTs.  
20" W. Oak now 21" S.45°W., 71.5', scribe visible.  
9" Laurel, now dead, N.45°E., 32.4'  
As notes, 1/4 sec. corner lies in old fence corner, running N-S  
& E.  
New BT - 20" D. Fir, S.89°E., 57.8' scribed "1/4 S23 CS BT"

Fd. OK by W. Ruppert, Sept. 1983, M 94-75 A & B.  
Fd. Ok by W. Ruppert, Oct. 1994, 1994-110 A,B, & C

Kristian DeGroot - For: Philip Johnson - Jan. 2014 - M167-18

-----  
Found - A 1" iron pipe by Markham in 1952 per CS 40/386,  
firmly set, projecting 2" above the ground in  
down ancient N-S-E fence lines. I set a yellow  
plastic cap, cap marked "BTS ENG-SURV" in the top  
of the iron pipe  
From which the remains of a BT by Markham:  
A root hole, w/down & rotting 9" Laurel alongside,  
bears N.45°E., 32.4' and a BT by Byron in 1968  
per CS 54/74:  
A 26" D.Fir bears S.87°30'E., 57.3' with a fully  
healed single blaze (S.89°E., 57.8')

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - A 12" D, Fir bears S.52°30'W., 22.7' scribed "¼ S22 BT"

New RMs- A 5/8" iron rod bears N.44°05'03"E., 32.43' (in the root hole)

A 5/8" iron rod bears N.64°40'01"W., 29.42'

All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown & distances are measured to a nail in the root crown at the side and center of the tree with a Total Station. All BTs have a 6" red band painted around the tree and the blazed face painted red and BT signs nailed to the tree. All new 5/8" x 30" iron rod reference monuments have a plastic cap stamped "BTS ENG-SURV".

NAD 83 (2011) EPOCH 2010.00

Latitude: 43°02'04.40706"N Longitude: 123°15'58.03327"W