

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO Survey by - Addison R. Flint, Deputy Surveyor Under Contract #56, dated April 1855 (DCSO records Vol. 17 Page(s) 7208)

Set quarter sec. post from which a
 Laurel 18" dia., bears S.35°W., 131 lks. dist.
 Pine 6" dia., bears N.38°E., 8 lks. dist.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19208)

Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30S R6W

¼

S3 S2

1990

from which

 A fir, 9 ins. diam., bears S. 87° E., 43 lks. dist., mkd.
 ¼ S2 BT.

 A cedar, 7 ins. diam., bears N. 15° W., 20 lks. dist.,
 mkd. ¼ S3 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.