

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35; and 2 of T.31-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7192-93)

Set quarter post, from which
B.Oak 22" dia., bears N.75°W., 177 lks.
B.Oak 15" dia., bears S.50°W, 99 lks.

Doug. County Surveyors Office - Ben B. Irving - Wit: Richardson; Godfrey; Kershner - Oct. 4, 1946 - C.S. File 38/135

Set a 3" x 3" x 30" Cedar stake scribed " ¼ S35 on N. face, "¼ S2 on S. face and "CS" on E. face. Drove a 1/2" x 48" auto steering rod alongside. Mound of dirt 18" high, 30" base.
Found - Orig. BT SW quad. standing with blaze chopped out, all scribe marks rotted off.
NW quad. BT rotted away but part of old stump still visible. Bearing and dist. check orig. field notes.
This corner is at the corner of old fences.
New BTs -18" Cedar bears N.74°W., 47.6 ft. mkd. "¼ S35 CSBT"
14" Fir bears S.3°W., 36.4 ft. mkd. "¼ S2 CS BT".

Searched for, not found. Feb. 1967, JMP, Doug. County Surveyors Office -

Doug. County Surveyors Office - James W. Byron, - For: BLM May 12, 1969 - C.S. File 54/86; M 37-62

Corner set from survey at proportionate distance.
Set Brass cap at ¼ cor. mkd: County Surveyor's T 30 S R 6 W
Office S 35
1969 S 2
T 31 S R 6 W
New BTs -16" D.Fir N.82°30'E., 22.6 ft. mkd. "¼ S35 CSBT".
12" W.Oak S.61°E., 100.1 ft. mkd. "¼ S2 CS BT".
Old N-S fence bears West, 49.0 ft.

Fd. Ok by R.Brown, April 1995 - M 119-61
Fd. OK by R. Dodge, Jan. 1997 - 1997-0020