

PRIMARY CORNER DESCRIPTION 1/4 Corner for Secs. 2 and 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7208)

Set quarter post from which
A B.Oak 8" dia., bears N.35°E., 14 lks. dist.
A Myrtle 2" dia., bears S.10°W., 5 lks. dist.

Herbert Northcraft - For: C & D Lumber Co. - May 2, 1974 - M 54-13

Set - 5/8" x 30" iron rod.
Old cor. not in evidence but new cor. compares with topography from old notes.
Set mound of rocks around rod from which
12" Cedar bears N.35½°W., 32.5 ft. scribed "¼ S2 T30S R6W BT 750
8" Incense Cedar bears S.46¼°E., 110.4 ft. scribed ¼ S11 T30S R6W BT 750.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19207-08)

Point for the ¼ sec. cor. of secs. 2 and 11 at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
T30S R6W
S2
¼
S11
1991

from which
A fir, 19 ins. diam., bears N. 34° E., 26½ lks. dist., mkd. ¼ S2 BT.
A fir, 13 ins. diam., bears S. 9° E., 8½ lks. dist., mkd. ¼ S11 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, a point established as the ¼ sec. cor. of secs. 2 and 11 by Herbert L. Northcraft, in 1974, bears S. 3° 12' 00" E., 2.250 chs. dist., monumented with a steel rod, 5/8 in. diam., projecting 7 ins. above ground, from which bearing trees mkd. by Northcraft:

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 11 ins. diam., bears S. $47\frac{1}{4}^{\circ}$ E., 167 lks. dist., with scribe marks $\frac{1}{4}$ S11 T30S R6W BT 750 visible on partially healed blaze.

A cedar, 16 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ W., 49 lks. dist., with scribe marks $\frac{1}{4}$ S2 T30S R6W BT 750 visible on partially healed blaze.

This point was established using improper control and is not utilized in this survey.