

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7202)

-----  
Set post cor. to secs. 1, 2, 11 and 12, from which  
A Laurel 8" dia., bears N.40°E., 113 lks. dist.  
A Red Fir 24" dia., bears N.35°W., 186 lks. dist.  
A Cedar 8" dia., bears S.75°E., 100 lks. dist.  
A Red Fir 30" dia., bears S.75°W., 113 lks. dist.

Douglas Co. Surveyors Office - Ben B. Irving, deputy -  
Witnesses: L.H. Smick; N.E. Richardson; Allen Moore - April  
and May 1929 - C.S. File 1/65 A & B; M 1-61; and "Old" cor.  
book, Pg. 183

-----  
**Note:** The records of corner descriptions of the Public Survey  
office in Portland does not agree with corners as found on  
ground. Remainder of field notes check reasonably close.  
After consultation with Dist. Attorney and Co. Surveyor and  
in view of the fact that no corners in field checked records  
and that age of corners corresponded with original work, it  
was decided to use field corners as the true corner and they  
were renewed accordingly.

-----  
From facing of two original BTs:  
Drove a 3/4" x 36" Galv. I.Pipe in a mound of rock.  
Original BTs:  
A Pine 24" dia., bears S.85°E., 117 lks.  
A Pine 24" dia., bears N.50°E., 38 lks.  
New BTs:  
A Fir 10" dia., bears S.00°50'W., 47 lks. blazed & scribed  
T30S R6W S11 CS BT.  
A Fir 14" dia., bears N.85°00'W.. 39 lks. blazed & scribed  
T30S R6W S2 CS BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike  
Darby; Jim Halterman - Jan. 1964 - C.S. File 53/40-14

-----  
Found - I.P. and rock mound at corner.  
Find bearing trees as recorded by Irving, except now  
16" R.Fir bears N.75°W., not N.85°W., 25.7 ft.  
SE BT, now dead.  
Note: 26" Pine to SE shows scribing on old face but by  
ring count, was scribed about 60 years ago.  
Corner agrees with call to stream. (66 ft. West)  
We find no orig. BTs but this is an area with right species.  
New BTs -14" R.Fir S.85°E., 17.6 ft. scribed S12 T30S R6W CSBT  
16" R.Fir N.41°E., 23.8 ft. scribed S1 T30S R6W CSBT  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Douglas Co. Surveyors Office - Randall Smith; Stephen Flause; Terrie Franssen - May 23, 1991 - C.S. File 64/15-7

CORNER REPORT ONLY

Found - 1" I dia., I.Pipe, protrudes 2" above ground. I.P. is surrounded by 3 ft. dia. ring of stones.

24" now 26" dia. down and dead pine with an opened double blaze, scribing visible "S BT", root hole bears S.85°E., 77.2 ft. Source unknown.

24" now 33" dia. Pine with a previously opened blaze, illegible scribe mark visible, bears N.54½°E., 61.4 ft. (agrees with recent BLM survey BT tags.) Source unknown.

10" now 21" dia., D.Fir with a recent rescribed single blaze, scribing visible "T30S R6W S11 BT" bears S.2°W., 31.0 ft. (agrees with recent BLM survey BT tags).

14" now 21" dia., D.Fir with a fully healed double blaze, bears N.75°W., 25.7 ft.

14" now 19" dia., D.Fir with a fully healed single blaze bears S.85°E., 17.6 ft.


16" now 16" dia., D.Fir with a fully healed double blaze bears N.41°E., 23.8 ft.

Iron pipe is 48 ft. East of a south running creek.  
(See CS File 64/15 for BLM problems and notes)

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19198-99)

Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



from which

- A cedar, 7 ins. diam., bears N. 28½° E., 27 lks. dist., mkd. T30S R6W S1 BT.
- A cedar, 9 ins. diam., bears S. 55° E., 60 lks. dist., mkd. T30S R6W S12 BT.
- A myrtle, 7 ins. diam., bears S. 74° W., 20 lks. dist., mkd. T30S R6W S11 BT.
- A fir, 16 ins. diam., bears N. 20½° W., 47½ lks. dist., mkd. T30S R6W S2 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, a point established as the cor. of secs. 1, 2, 11, and 12 by Irving, in 1929, and perpetuated by Byron, 1964, bears S. 3° 10' 00" E., 4.480 chs. dist., monumented with an iron pipe, 3/4 in. diam., in a collar of stone, projecting 2 ins. above the ground, from which the remains of bearing trees, not of record, found by Irving:

A pine, 35 ins. diam., bears N. 54½° E., 93 lks. dist., with scribe mark C visible on previously opened blaze.

A root hole, bears S. 86° E., 113 lks. dist., with a down pine alongside, 30 ins. diam., with scribe mark C visible on previously opened blaze and BT on newly opened blaze.

and bearing trees mkd. by Irving

A fir, 22 ins. diam., bears S. 1° W., 47 lks. dist., with healed blaze.

A fir, 21 ins. diam., bears N. 75° W., 39 lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A fir, 14 ins. diam., bears N. 41° E., 36 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears S. 85° E., 27 lks. dist., with healed blaze.

This point was determined by Irving at the intersection of the facing of the two bearing trees of unknown origin or record, it is not harmoniously related with identified existing original corners in the area, and is not utilized in this survey.