

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36 of T29-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6457)

Set a post, at proper dist., cors. 1, 2, 35 & 36, from which
A B.Oak 7" dia., bears N.60°W., 73 lks.
A W.Oak 4" dia., bears S.85°W., 125 lks.
A W.Oak 6" dia., bears N.12°E., 90 lks.
A W.Oak 6" dia., bears S.30°E., 89 lks.

Ben B. Irving, D.C.S. - Wit: N.E. Richardson; Allen Moore -
For: Marks and Wollenberg - April/May 1929 - C.S. File 1/65;
M 1-61; Vol. 3 Pgs. 294-96

Position identified by four original BTs and hole filled with rotten wood as part of original stake.

Set a 5" x 60" Fir post in mound of rock. Original BTs:

B.Oak 12" dia., N.47°17'E., 91 lks., dead & rotting.
B.Oak 8" dia., S.20°11'E., 46 lks., orig. scribe marks.
Pine 36" dia., N.37°19'W., 56 lks.
Pine 30" dia., S.34°20'W., 41 lks.

Replaced Oak BTs:

Fir 12" dia., N.75°28'E., 12 lks. blazed & scribed "T29S R6W S36 CS BT".
Fir 13" dia., S.38°20'E., 9 lks. blazed & scribed "T30S R6W S1 CS BT".

Doug. County Surveyors Office - James W. Byron, Deputy - For:
Dale Weekly - May 15, 1956 - C.S. File 47/93

Found - Mound of rock and scribed post at corner.

All BTs as renewed by Irving, in good condition.

Set an I.P. with B. Cap mkd: 35|36 1956, T30S R6W
Co. Surveyor's Office 2|1

Blazed and scribed:

12" R.Fir S.36°W., 22.0 ft. "T30, S2 CS BT".

Kris DeGroot - For: C & D Lumber Co. - 6/2003 - M 142-44

Found - 1" iron pipe by Byron in 1956, firmly set, projecting 14" above the ground with 2½" brass cap (properly) stamped, from which an orig. BT by Ford in 1854 as recorded by Irving in 1929:

36" Pine stump bears N.38°20'W., 37.3 ft. (rec. N.37°19'W., 56 lks.)

And BTs by Irving in 1929, RM 1-61

24" D.Fir bears S.37°14'E., 4.8 ft. with healed blaze. (rec. S.38°20'E., 9 lks.)

continued next page

