

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7198)

-----  
Set ¼ sec. post, from which  
    A Laurel 2" dia., bears N.85°E., 30 lks. dist.  
    A Laurel 4" dia., bears S.80°W., 40 lks. dist.

Briggs for James Blundell - June 14, 1878 - Vol. 2 Pg. 286;  
Vol. 3 Pg. 251 and C.S. File 3/37

-----  
No evidence of corner.  
Set post marked N. B. T.  
B.Oak 4" dia., bears North 7 lks.  
B.Oak 5" dia., bears S.70°E., 14 lks.

J.H. Markham L.S. #2880 - Oct. 20, 1949 - C.S. File 40/188-2

-----  
Determined from a probable BT, Oak stump which bears East 30.0 ft.  
Set a wood stake, from which  
    7" Laurel bears North 27.0 ft. mkd. S25 ¼ S 2880 BT.  
    6" Laurel bears S.33°E., 23.0 ft. mkd. S36 ¼ S 2880 BT.  
There is a fence running west and south from this corner, it being 470 ft. west to the centerline of Shoestring Road.

Glenn Baughman for Kinsey Lancaster - Dec. 1973 - C.S. File 55/331; M 52-1

-----  
Set - 1½" I.P. with brass cap 24" in ground mkd:  
    T.30S. R.6W ¼ 25 OLS 536 1973  
                                    36  
BTs - 6" madrone bears N.16½°E., 11.6 ft. scribed ¼ S25 BT.  
    6" D.Fir bears S.2¼°W., 8.2 ft. scribed ¼ S36 BT.  
Corner lies on north south ridge approx. 185 ft. from Twp.  
Added 6/25/2020: 1/4 corner set by Markham bears N.89°17'12"W 87.39' and S.0°42'48"W. 21.07

Fd. OK - Donald Bentz - March, 1986 - M 101-1  
Fd. Ok - Raymond Brown - March, 1997 - 1997-0049  
Fd. OK - W. Ruppert, Jan. 2002 see M137-71 (invalid BLA)

Carl Sweeden - For: Mike Swett - 3/2015 - M169-11 & M169-75

-----  
Found - 2½" BC "OLS 536 1973"  
    10" Madrone BT, N.16½°E., 11.6' scar vis.  
    14" D.Fir BT, S.2¼°W., 8.2' scar vis.