

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Vol. 17 Page 7202)

Set quarter sec. post, from which
Pine 12" dia., bears N.70°E., 38 lks. dist.
Pine 15" dia., bears S.35°W., 110 lks. dist.
Summit of ridge.

Bruce R. Rogers, Deputy - For: C & D Lumber Co. - March 1965
C.S. File 53/117 & M 22-65

Set by proration.
Set brass cap in mound of rocks mkd:
County Surveyors T30S R6W
Office 1965 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{1}{12}$
New BTs -14" Pine bears N.33°E., 148.0 ft. mkd. $\frac{1}{4}$ S1 CS BT.
8" Oak bears S.4°E., 85.5 ft. mkd. $\frac{1}{4}$ S12 CS BT.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19201)

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock, supported in a mound of stone, 8 ft. base, to top, with brass cap mkd.

T30S R6W
S1
 $\frac{1}{4}$)))))
S12
1991

from which

- A pine, 20 ins. diam., bears N. 82° E., 60 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
- A pine, 19 ins. diam., bears S. 42 $\frac{1}{4}$ ° W., 76 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

From this point, a point established as the $\frac{1}{4}$ sec. cor. of secs. 1 and 12 by Bruce R. Rogers, 1965, bears S. 3° 12' 00" E., 2.220 chs. dist., determined from bearing trees mkd. by Rogers:

- A pine, 19 ins. diam., bears N. 35 $\frac{1}{2}$ ° E., 224 lks. dist., with healed double blaze.
- An oak, 12 ins. diam., bears S. 1 $\frac{1}{2}$ ° W., 130 lks. dist., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The point was established using improper control and is not utilized in this survey.

From this same point, a bearing tree not of record found by Irving, Deputy County Surveyor, in 1929, bears S. 9° 40' 00" E., 3.920 chs. dist.; an oak, 28 ins. diam., with scribe mark C visible on opened rotted blaze, facing E.

Fd. BC by G. Lang, 5/2011 - M162-47
Fd. BC by G. Lang, 2/2013 - M164-69