

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T30-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7130)

-
- Set a post cor. of secs. 13, 18, 19 and 24, from which
- A B.Oak 20" dia., bears S.40°E., 200 lks.
 - A B.Oak 10" dia., bears N.62°E., 264 lks.
 - A B.Oak 10" dia., bears S.9°W., 475 lks.
 - A B.Oak 12" dia., bears N.85°W., 50 lks.

G.G. Stewart, Deputy - Witnesses: J.M. Yocum; B. Bates; J.M. Yocum - Dec. 16, 1921 - C.S. File 7/14; Vol. 3 Pg. 105 and "old" cor. Bk. Page 148

-
- Reset from stump of original BT, others gone. Set Iron pipe for corner, from which
- A 12" B.Oak bears N.63°W., 68.3 ft.
 - A 12" W.Oak S.72°W., 25.0 ft.
 - An 18" W.Oak N.42°E., 72.5 ft.
 - A 12" W.Oak S.69°E., 220.0 ft.

BLM resurvey by Roseberry and Jelley, under Group #662. Survey, Oct. 1967-June 1969 (DCSO records, Vol. 38 Page 15557)

Corner perpetuated & recorded by G.G. Stewart, 1921, monumented with an iron pipe 1½" dia., 30" long, firmly set, projecting 8" above ground, from which the remains of the original bearing tree:

- A decayed Oak stump, size indeterminate, bears S.40°E., 200 lks. dist., no marks visible.
- and bearing trees mkd. by Stewart
- A W.Oak 19" dia., bears N.41°E., 109 lks. dist., with healed double blaze.
 - A W.oak 17" dia., bears S.72°W., 38½ lks. dist., with healed double blaze.
 - A B.Oak 13" dia., bears N.63°W., 102 lks. dist., with scribe mark 6 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S T 30 S
R 6 W S 18
S 24 S 19
R 5 W
1969

from which a new bearing tree

- An Oak 13" dia., bears S.23°E., 15 lks. dist., mkd. T30S R5W S19 BT.

Reset iron pipe alongside iron post.