

TOWNSHIP 30 RANGE 06 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7196)

Set post, cor. to secs. 13, 24, 18 and 19, from which
A W.Oak 20" dia., bears S.63°E., 10 lks.
A W.Oak 18" dia., bears S.60°W., 104 lks.
A W.Oak 22" dia., bears N.65°W., 50 lks.
A W.Oak 16" dia., bears N.28°E., 69 lks.

John H. Markham, Jr. - For: Riddle Mfg. Co. - Jim Loper, witness - Feb. 9, 1953 - C.S. File 41/113-1

As determined by O.B.T.,
A B.Oak stump bears N.65°W., 40 ft.
A W.Oak stump 25" bears S.60°W., 69 ft.
At corner set ½" x 20" I.P. from which
W.Oak 30" bears S.76°W., 89.5 ft. mkd. S24 T30S R6W BT.
Laurel 9" bears N.67°W., 21.0 ft. mkd. S13 T30S R6W BT.
Fences running N-S-W from corner. Fence Cor. bears North 7 ft.

Bruce Shaner - For: Roseburg Resources Co. - June 2002 - M137-44 & C.S. File 65/44-6 M

Found - ½" iron pipe by Markham not found, but set a ¾"x40" iron rod with 2½" alum. cap, mkd:
ROSEBURG RESOURCES CO.
T30S R6W
S 13 |
S 24 |
RLS 430 2002 from which a:
36" W.Oak, orig., old rotten face with axe marks, bears S.60°W., 69.0 ft. to face. (Markham called it a stump)
36" W.Oak, face overgrown, bears S.82°W., (rec. S.76°W.) 89.5 ft. to face.
16" Madrone, scribes not visible, I bark scribed "T30S R6W S13 BT" bears N.67°W. 21.0 ft to center
New - 8" Madrone, bark scribed "T30S R6W S13 BT" bears N.65°W., 12.3 ft. to center.
6 ft. steel fence post North 1.0 ft.
Note - Alum. cap & iron pipe is South, 6 ft. from fence corner, fence runs North & West from corner.

Fd. ¾" IP w/AC 8/2021 by R. Badgley - M178-40